

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

## FIELD NOTES

DEPENDENT RESURVEY OF  
THE SOUTH BOUNDARY (UINTAH SPECIAL BASE LINE),  
A PORTION OF THE EAST BOUNDARY,  
A PORTION OF THE SUBDIVISIONAL LINES,  
AND THE  
RESURVEY AND SURVEY OF PORTIONS  
OF THE  
SUBDIVISION OF SECTIONS 33 AND 34,  
INCLUDING THE  
INVESTIGATIONAL RETRACEMENT SURVEY  
OF THE  
SOUTH, EAST, AND WEST BOUNDARIES,  
AND THE  
FIRST AND SECOND LATITUDINAL SECTION LINES,  
A PORTION OF THE SUBDIVISIONAL LINES OF SECTIONS  
25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35 AND 36,

IN  
TOWNSHIP 1 NORTH, RANGE 4 WEST

OF THE UINTAH SPECIAL MERIDIAN  
IN THE STATE OF UTAH

EXECUTED BY

*Jerry L. Thomas*  
*Cadastral Surveyor*

Under special instructions dated *April 9, 1992*, approved *April 9, 1992*, which provided for the surveys included under Group Number *781*, and assignment instructions dated *April 15, 1992* and *March 17, 1997*.

Survey commenced *September 16, 1992*

Survey completed *May 29, 1997*

## INDEX DIAGRAM

Township 1 North, Range 4 West						
24						21
24 6	5	4	3	2	1	20
24						20
24 7	8	9	10	11	12	20
23						19
23 18	17	16	15	14	13	19
23						19
23 19	20	21	22	23	24	18
22 32	31 31	31 30	30 30	30 29	29 29	18
						18
22 30	37 29	36 28	35 27	34 26	33 25	17
22 28	28 27	27 27	27 26	26 26	25 25	16
						16
21 31	36 32	36 33	34 34	33 35	32 36	15
14 13	12 11	10 9	8 7	6 6	5 4	3

The Survey & Resurvey of the Subdivision of Section 33 ....Page 37

The Survey & Resurvey of the Subdivision of Section 34 ....Page 40

## TOWNSHIP 1 NORTH, RANGE 4 WEST, UINTAH SPECIAL MERIDIAN, UTAH

**CHAINS**

The following field notes describe the dependent resurvey of the South boundary ( Uintah Special Base Line), and a portion of the East boundary, along with a portion of the subdivisional lines and the resurvey and survey of the subdivision of sections 33 and 34, by the Three Mile Method. Included with this survey is an Investigational Retracement Survey of the South, East, and West boundaries, the First and Second Latitudinal Section Lines, and a portion of the subdivisional lines of 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, and 36, for Township 1 North, Range 4 West, Uintah Special Meridian, Utah.

**History of Surveys**

Surveyed by		Retr. or Resurveyed by	
South BOUNDARY (Uintah Special Base Line)			
All	D.G. Major	1882	
East BOUNDARY			
All	D.G. Major	1882	
All		H.D. Heist	1903
West BOUNDARY			
All	D.G. Major	1882	
North BOUNDARY			
All	D.G. Major	1882	
All		J.C. Dick & A.K. Tiernan	1903
SUBDIVISION (All by 3 Mile Method except Section 27)			
All	D.G. Major	1882	
REMONUMENTATION			
Portion	A. Nelson	1961	

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 781, dated April 9, 1992. Particular attention was given to section ( 6-7 ), of the Manual with reference to retracement. Extensive on the ground retracement was conducted to properly consider interfering private rights and afford new evidence to identify the true character and condition of the previous survey.

## TOWNSHIP 1 NORTH, RANGE 4 WEST, UINTAH SPECIAL MERIDIAN, UTAH

**CHAINS**

Investigational Retracement Survey has been made for the following reasons:

- a. Ascertain the direction and length of lines between existing fragmentary controlling monuments.
- b. Verify if fraudulent surveys exist and identify the location of missing monumentation for comparison with existing ground evidence.

It was necessary to retrace several miles of line from one existing corner to the next controlling corner to recover supplement evidence needed to establish justification for acceptance of local control for subdivision of sections 33 and 34. The First and Second Latitudinal Section Lines were surveyed on a true latitudinal curve with quarter-section and section corner marked with temporary points at single proportionate distance East and West.

Extensive retracement was necessary to support ground evidence and protect the bona fide rights of the claimants. These Investigational Retracement measurements "Do Not" purport to be resurvey boundaries. The results of having retraced 36 miles of investigational line has provided sufficient proof of nonsupportive monumentation within the interior of the township.

The recommendation for future survey work would show justification for an Independent Resurvey with the establishment of new section lines and without reference to the original survey. It would be necessary to preserve the boundaries of those lands within sections 29, 33, 34, and 36 patented by legal subdivision, with a metes and bounds survey to designate the tracts of land to be excluded from the Independent Resurvey.

The directions of lines were determined by hour angle observations of the sun and Polaris, carried forward by sustained angulation. Distances were determined by electronic measurement.

Preliminary to the Dependent Resurvey, an Investigational Retracement Survey of the South, East, and West boundaries, the First and Second Latitudinal Section Lines, and the Subdivisional Lines for sections 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, and 36. Also the Subdivision of sections 33 and 34 were retraced for original monumentation and a diligent search was made for any evidence of the original field note record.

Controlling identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The Investigational Retracement Survey data was verified and included with the true line notes.

Monuments marked 1992 within the subdivision of sections 33 and 34, were monumented by Richard A. Zaninovich, Cadastral Surveyor, under this same group number, prior to his transfer from Utah and issuance of Supplement Assignment Instructions.

The geographic position of the South East township corner on the Uintah Special Base Line, as determined by Global Positioning System, is as follows:

Latitude 40°25'54.5290" N.  
N.A.D. 1983 ( 1994 )

Longitude 110° 16 39.4576" W.

## TOWNSHIP 1 NORTH, RANGE 4 WEST, UINTAH SPECIAL MERIDIAN, UTAH

**CHAINS**

This corner is designated as a B.L.M. control station.

The mean magnetic declination as projected from the U.S. Geological Survey Magnetic Declination Map of 1990, is: 13° E.

---

Investigational Retracement Survey and Dependent Resurvey  
For the South Boundary, (Uintah Special Base Line),  
Township 1 North, Range 4 West, Uintah Special Meridian, Utah

---

Reestablishment of the Survey Executed by D.G. Major in 1882

---

Beginning at the South-East standard township corner of T. 1 N., R.4 W., monumented with a Sandstone 14 x 10 x 6 ins., plainly marked with 6 notches on the North and West edges. ( Record: Sandstone 15 x 12 x 12 ins. marked SC on the North face, and 6 grooves on all three sides, North, East, and West faces, encircled by a large mound of stone. )

There is no remaining evidence of the following original bearing trees.

( Record: A cedar, 15 ins., diam., bears N. 71° 30' E., 28 links dist., )  
( Record: A cedar, 10 ins., diam., bears S. 66° 00' E., 11 links. dist., )  
( Record: A cedar, 13 ins., diam., bears S. 50° 00' W., 21 links dist., )  
( Record: A cedar, 10 ins., diam., bears N. 41° 15' W., 08 links dist., )

At the corner point

Set an aluminum post, 30 ins., long, 2 1/2 ins. diameter, 24 ins. in the ground, with aluminum cap marked.

	SC	
T1N		T1S
R4W		R3W
S36		S6

1995

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone North-West of the corner.

Corner is located South, one link distance from fence corner, with fences projecting North and West.

INVESTIGATIONAL RETRACEMENT SURVEY AND DEPENDENT RESURVEY  
FOR THE SOUTH BOUNDARY, (UINTAH SPECIAL BASE LINE),  
T. 1 N., R. 4 W., UTAH SPECIAL MERIDIAN, UTAH

**CHAINS**

From this corner point, the North-East Township corner of T. 1 S., R. 4 W., bears N. 89° 41.0' E., 9.505 chains distance, monumented with a Sandstone, 14 x 10 x 8 ins., firmly set, projecting 10 ins. above ground, plainly marked 6 notches on the South and West edges, encircled by a scatter mound of stone. ( Record: Sandstone, 26 x 16 x 12 ins., marked CC with 6 grooves on South face and 6 grooves on East and West face, encircled by a mound of stone 3 ft. diam. at base and 1 ft. high ).

There is no remaining evidence of the following original bearing trees.

( Record: A cedar, 9 ins., diam., bears N. 57° 00' E., 12 links dist., )  
( Record: A cedar, 8 ins., diam., bears S. 51° 00' E., 11 links dist., )  
( Record: A cedar, 12 ins., diam., bears S. 48° 30' W., 14 links dist., )  
( Record: A cedar, 16 ins., diam., bears N. 66° 00' W., 17 links dist., )

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins., diameter, 24 ins. in the ground, and in a collar of stone, with aluminum cap marked.

T1S      R3W

S1
T1S      R4W
1995

Deposit the marked stone alongside the aluminum post

From this corner point, a private survey marker, bears West, 3 links distance, a rebar with plastic cap marked 3995.

S. 89° 49.6' W., on the South boundary of section 36, for T.1 N., R.4 W., along the true Latitudinal curve line between controlling corners.

Descend over NW slope through juniper and cedar.

**19.966** Point for the standard East 1/16 section corner of section 36 only, on the South boundary of the Township, at proportionate distance; there is no remaining evidence of the original corner; ( Record: Sandstone 14 x 12 x 8 ins., marked 1/16 on East face, encircled by a mound of stone 3 ft. at base and 1 ft. high ).

**NOTE:** Corner not monumented.

**21.000** Bottom of ravine, drains South-East.

**39.932** Point for the standard 1/4 corner of section 36 only, on the South boundary of the Township, at proportionate distance; there is no remaining evidence of the original corner; ( Record: Sandstone 20 x 10 x 8 ins., marked SC 1/4 on East face, encircled by a mound of earth, 3 ft. diam. at base and 1 ft. high ).

**NOTE:** Corner not monumented.

INVESTIGATIONAL RETRACEMENT SURVEY AND DEPENDENT RESURVEY  
FOR THE SOUTH BOUNDARY, (UINTAH SPECIAL BASE LINE),  
T. 1 N., R. 4 W., UTAH SPECIAL MERIDIAN, UTAH

**CHAINS**

Corner point is located South, 68.1 links distance, from a fence line extending East and West, and falls on top of bluff.

- 59.898** Point for the standard West 1/16 section corner of section 36 only, on the South boundary of the Township, at proportionate distance; there is no remaining evidence of the original corner; ( Record: Sandstone 12 x 10 x 7 ins., marked SC 1/16 on East face, encircled by a mound of earth and stone, 3 ft. diam., at base 1 ft. high ).  
**NOTE:** Corner not monumented.

- 79.864** Point for the standard corner of sections 35 and 36, on the South boundary of the Township, at proportionate distance; there is no remaining evidence of the original corner. ( Record: Sandstone 14 x 12 x 9 ins., marked SC with 6 grooves on North face and 1 groove on East face, encircled by a mound of earth and stone 3 ft. diam., at base and 1 1/2 ft. high ).

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 24 ins. in the ground in a collar of stone, with aluminum cap marked:

SC	
T1N	R4W
S35	S36
1997	

Set a 6 ft. steel fence post alongside the aluminum post.

Corner is located South, 1.39 chains distance from a four strand barbed wire fence.

---

S. 89° 49.6' W, on the South boundary of section 35, for T. 1 N., R.4 W., along the true Latitudinal curve line between controlling corners.

- 19.966** Point for the standard East 1/16 section corner of section 35 only, on the South boundary of the Township, at proportionate distance; there is no remaining evidence of the original corner. ( Record: Sandstone 10 x 8 x 8 ins., marked SC 1/16 on East face, encircled by a mound of earth, 3 ft. diam. at base, and 1 ft. high. )  
**NOTE:** Corner not monumented.

- 39.932** Point for the standard 1/4 section corner of section 35 only, on the South boundary of the Township, at proportionate distance; falls on a ditch bank, there is no remaining evidence of the original corner. ( Record: Sandstone 9 x 8 x 8 ins., marked SC 1/4 on East face, encircled by a mound of earth 3 ft. diam., at base and 1 ft. high ).

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

INVESTIGATIONAL RETRACEMENT SURVEY AND DEPENDENT RESURVEY  
FOR THE SOUTH BOUNDARY, (UINTAH SPECIAL BASE LINE),  
T. 1 N., R. 4 W., UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

SC  
T1N R4W  
1/4 S35  
-----  
1997

Set a steel fence post alongside the aluminum post.

Corner is located South, 2.06 chains distance from a 4 strand barbed wire fence extending East and West, and is also located North, 93 links distance from a 4 strand barbed wire fence extending East and West.

- 59.898** Point for the standard West 1/16 section corner of section 35 only, on the South boundary of the Township, at proportionate distance; there is no remaining evidence of the original corner. ( Record: Sandstone 12 x 10 x 8 ins., marked SC 1/16 on East face, encircled by a mound of earth 3 ft. diam. and 1 ft. high ).  
**NOTE:** Corner not monumented.

- 79.864** Point for standard corner of section 34 and 35, on the South boundary of the Township, at proportionate distance, falls on top of old wooden post 18 ins. long with ax marks, buried below surface of ground. This post appears to have been used as an old line stake. There is no other evidence of the original corner. ( Record: Sandstone 12 x 10 x 8 ins., marked SC with 6 grooves on North face and 2 grooves on East face, encircled by a mound of earth 3 ft. diam. at base and 1 ft. high ).

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

SC  
T1N R4W  
S 34 | S 35  
-----  
1997

Buried old wooden stake alongside aluminum post.

Set a steel fence post alongside aluminum post.

Corner is located near North-West corner of water storage pond.

S. 89° 49.6' W., on the South boundary of section 34, for T. 1 N., R. 4 W., along the true Latitudinal curve line between controlling corners.

- 19.966** Point for the standard East 1/16 section corner of section 34 only, on the South boundary of the Township, at proportionate distance; there is no remaining evidence of the original corner. ( Record: Sandstone 9 x 9 x 8 ins., marked SC 1/16 on East face, encircled by a mound of earth 3 ft. diam. at base and 1 ft. high ).  
**NOTE:** Corner not monumented.



INVESTIGATIONAL RETRACEMENT SURVEY AND DEPENDENT RESURVEY  
FOR THE SOUTH BOUNDARY, (UINTAH SPECIAL BASE LINE),  
T. 1 N., R. 4 W., UINTAH SPECIAL MERIDIAN, UTAH

**CHAINS**

- 39.932** Point for the standard 1/4 section corner for section 34 only, on the South boundary of the Township, determined latitudinally by the true latitude curve between controlling corners and longitudinally by old fence line projecting North. There is no remaining evidence of the original corner; ( Record: Sandstone 22 x 16 x 9 ins., marked SC 1/4 on East face, encircled by a mound of earth 3 ft. diam. at base and 1 ft. high ).

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 36 ins. in the ground, 6 ins. below the surface of the road, with aluminum cap marked:

SC  
T 1 N R 4 W  
1/4 S 34

T1S  
1997

from which

An aluminum post, 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, with a collar of stone, bears N. 45° E. 60.6 links dist. with aluminum cap marked RM T 1 N R 4 W 1/4 S 34 1997 40 FT, and an arrow pointing to the corner.

An aluminum post 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 55° W., 50 links dist., with an aluminum cap marked: RM T 1 N R 4 W 1/4 S 34 1997 33 FT., and an arrow pointing to the corner.

- 60.105** Point for the standard West 1/16 section corner of section 34 only, on the South boundary of the Township, at proportionate distance; there is no remaining evidence of the original corner. ( Record: Sandstone 12 x 10 x 9 ins., marked SC 1/16 on East face, encircled by a mound of earth 3 ft. diam.at base and 1 ft. high ).  
**NOTE:** Corner not monumented.

- 68.435** Local corner bears North, 19.6 links dist. for the CC of Section 3 and 4, T.1 S., R. 4 W., monument with a metal cap 1/2 ins. diam., marked: LS 148951 set flush with asphalt, and in the middle of a 3-way road intersection, projecting East and West and South, This ground evidence agrees with record from Duchesne County Surveyor.

- 80.278** Point for the standard corner of sections 33 and 34, on the South boundary of the Township, determined latitudinally by the true latitude curve between controlling corners and longitudinally by an old fence line projecting North. There is no remaining evidence of the original monument. ( Record: Sandstone 16 x 12 x 5 ins., marked SC with 6 grooves on North face and 3 grooves on East face, encircled by a mound of stone, 3 ft. diam. and 1 ft. high ).

INVESTIGATIONAL RETRACEMENT SURVEY AND DEPENDENT RESURVEY  
FOR THE SOUTH BOUNDARY, (UINTAH SPECIAL BASE LINE),  
T. 1 N., R. 4 W., UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 24 ins. in the ground, with aluminum cap marked:

SC	
T1N	R4W
S33	S34
<hr/>	
1997	

from which a T-iron with a 1 inch cap, bears North 31 links dist.

Raise a mound of stone North of corner.

Corner is located North, 1 lk. distance from a East and West fence and South, 31 links distance from a East and West gravel road.

S. 89° 49.6" W., on the South boundary of section 33 for T. 1 N., R. 4 W., along the true Latitudinal curve line between controlling corners.

20.310

Point for the standard East 1/16 section corner of section 33 only, on the South boundary of the Township, determined latitudinally by true latitude curve between controlling corners and longitudinally by an old fence line projecting North. There is no remaining evidence of the original monument. ( Record: Sandstone 12 x 10 x 6 ins., marked SC 1/16 on East face, encircled by a mound of earth, 3 ft. diam. and 1 ft. high ). Corner is located near a fence line projecting West.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a mound of stone, 3 1/2 ft. base, to top, with aluminum cap marked:

SC	
T1N	R4W
E 1/16	S33
<hr/>	
1997	

Set a 6 ft. steel fence post alongside the aluminum post.

Corner is located near edge of small irrigation ditch, and South, 45 1/2 links distance from a East and West fence line, and South, 72 links distance from center line of gravel road extending East and West.

INVESTIGATIONAL RETRACEMENT SURVEY AND DEPENDENT RESURVEY  
FOR THE SOUTH BOUNDARY, (UINTAH SPECIAL BASE LINE),  
T. 1 N., R. 4 W., UTAH SPECIAL MERIDIAN, UTAH

## CHAINS

40.081

Point for the standard 1/4 section corner of section 33 only, on the South boundary of the Township, determined latitudinally by true latitude curve between controlling corners, and longitudinally by an old fence line projecting North. There is no remaining evidence of the original monument. ( Record: Sandstone 13 x 11 x 6 ins., marked SC 1/4 on East face, encircled by a mound of earth, 3 ft. diam. at base and 1 ft. high ). Corner is located near a fence line projecting West.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

SC  
T1N R4W  
1/4 S33  
-----  
1997

Set a 6 ft. steel fence post alongside the aluminum post.

Corner is located at North end of pasture field, South, 60 links distance from fence line extending East and West and South, 100 links distance from center line of gravel road extending East and curving North-Westerly.

48.054

Intersect fence line extending North and South, with a rebar and plastic cap marked LS 3817 that bears North, 11 links distance.

59.827

The standard West 1/16 section corner of section 33 only, on the South boundary of the Township, monumented with a Sandstone 12 x 6 x 5 ins. above ground, plainly marked 1/16 on North face, and a galvanized post, 2 1/2 ins. diam., alongside. ( Record: Sandstone 13 x 10 x 8 ins., marked SC 1/16 on East face, encircled by a mound of earth 3 ft. diam. at base and 1 ft. high ).

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

SC  
T1N R4W  
W 1/16 S33  
-----  
1997

Deposit the marked stone alongside the aluminum post.

Corner is located South, 3 links distance from an old fence line that extends East and West.

S. 89° 46.2' W., beginning new measurement, on the South boundary section 33, for T. 1 N., R. 4 W., along the true Latitudinal curve line between controlling corners.

**INVESTIGATIONAL RETRACEMENT SURVEY AND DEPENDENT RESURVEY  
FOR THE SOUTH BOUNDARY, (UINTAH SPECIAL BASE LINE),  
T. 1 N., R. 4 W., UTAH SPECIAL MERIDIAN, UTAH**

**CHAINS****10.441**

The closing corner of sections 4 and 5, T.1 S., R.4 W., monumented with a Sandstone 12 x 10 x 5 ins. above ground, plainly marked, 6 grooves on the South face, with a galvanized pipe, 2 1/2 ins. diam., alongside. ( Record: Sandstone 16 x 13 x 7 ins. marked CC with 6 grooves on South face, 4 grooves on East, and 2 grooves on West face, encircled by a mound of earth 3 ft. diam. at base and 1 ft. high. )

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a collar of stone, with aluminum cap marked:

T 1 N R 4 W

S5 | S4

C C

T1S R4W

1997

Deposit the marked stone and galvanized post alongside the aluminum post.

Corner is located South, 3 links distance from a 4 strand barbed wire fence extending East and West.

Continue alongside a four strand barbed wire fence.

**20.052**

The standard corner of section 32 and 33, on the South boundary of the Township, monumented with a Sandstone 8 x 8 x 6 ins. above ground, plainly marked, 4 grooves on East face and 2 grooves on the West face with SC on the North face. With a galvanized post 2 1/2 ins. diam., alongside. ( Record: Sandstone 12 x 10 x 9 ins., marked SC with 6 grooves on North face and 4 grooves on East face, encircled by a mound of earth 3 ft. diam. at base and 1 ft. high ).

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a collar of stone, with aluminum cap marked:

SC

T1N R4W

S32 | S33

1997

Deposit the marked stone alongside the aluminum post.

Corner is located South, 2.3 links distance from a 4 strand barbed wire fence extending East and West.

INVESTIGATIONAL RETRACEMENT SURVEY AND DEPENDENT RESURVEY  
FOR THE SOUTH BOUNDARY, (UINTAH SPECIAL BASE LINE),  
T. 1 N., R. 4 W., UTAH SPECIAL MERIDIAN, UTAH

## CHAINS

S. 89° 48.9' W., on the South boundary of section 32, for T. 1 N., R. 4 W., along the true Latitudinal curve line between controlling corners.

20.045

Point for the standard East 1/16 section corner of section 32 only, on the South boundary of the Township, at proportionate dist., there is no remaining evidence of the original corner; (Record: Sandstone with no dimensions marked SC 1/16 on East face, encircled by a mound of earth 3 ft. diam. at base and 1 ft. high ).

**NOTE:** Corner not monumented.

30.437

Point for the 1/4 corner of section 5 only, T. 1 S., R. 4 W., at midpoint between the closing corner of sections 4, and 5 and the closing corner of sections 5, and 6, and on the North boundary of section 5.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T 1 N R 4 W  
-----  
1/4 S5  
T1S R4W  
1997

Corner is located in fence line extending East and West.

40.090

The standard 1/4 section corner of section 32 only, on the South boundary of the Township, monumented with a Sandstone 12 x 8 x 6 ins. set alongside a fence post, plainly marked 1/4 on North face. ( Record: Sandstone 14 x 11 x 9 ins., marked SC 1/4 on East face, encircled by a mound of earth 3 ft. diam., at base and 1 ft. high ).

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

SC  
T1N R4W  
1/4 S32  
-----  
1997

Deposit the marked stone alongside the aluminum post.

Set a cedar fence post alongside the aluminum post.

S. 89° 40.9' W., beginning new measurement, on the South boundary of section 32, T. 1 N., R. 4 W., along the true Latitudinal curve line between controlling corners.

3.677

Intersect left bank of the Lake Fork River, drains South.

INVESTIGATIONAL RETRACEMENT SURVEY AND DEPENDENT RESURVEY  
FOR THE SOUTH BOUNDARY, (UINTAH SPECIAL BASE LINE),  
T. 1 N., R. 4 W., UINTAH SPECIAL MERIDIAN, UTAH

**CHAINS****3.979**

Point for the Meander Corner on left bank of the Lake Fork River, at proportionate distance; there is no remaining evidence of the original corner due to river erosion.  
( Record: Sandstone 14 x 10 x 8 ins., marked MC, encircled by a mound of earth 3 ft. diam. at base and 1 ft. high ).

**NOTE:** Corner not monumented, due to river bottom slough where it is impracticable to establish a permanent monument.

**19.931**

Point for the standard West 1/16 section corner of section 32 only, on the South boundary of the Township, at proportionate distance; there is no remaining evidence of the original corner.  
( Record: Sandstone 12 x 10 x 8 ins., marked SC 1/16 on East face, encircled by a mound of earth 3 ft. diam. at base and 1 ft. high ).

**NOTE:** Corner not monumented.

**30.395**

Point for the closing corner of sections 5 and 6, T.1 S., R.4 W., at proportioned distance, there is no remaining evidence of the original corner. ( Record: Sandstone 12 x 8 x 7 ins. marked CC with 6 grooves on South face, 5 grooves on East face and 1 groove on West face, encircled by a mound of earth 3 ft. diam. at base and 1 ft. high. )

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T1N R4W	
S32	
<hr/>	
S6	S5
C	C
T1S R4W	
1997	

Corner is located South, 6 links distance from a fence line extending East and West, and East, 24 links distance from fence line extending North and South.

**39.862**

The standard corner of sections 31 and 32, on the South boundary of the Township, monumented with a Sandstone, 5 x 5 x 5 ins. above ground, plainly marked, 5 grooves on the East face, and 1 groove on the West face, and an SC on the North face. Also with a galvanized post 2 1/2 ins. diam. alongside. ( Record: Sandstone 12 x 10 x 10 ins., marked SC with 6 grooves on North face and 5 grooves on East face, encircled by a mound of earth 3 ft. diam. at base and 1 ft. high ).

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 24 ins. in the ground, in a mound of stone, 3 ft. base, to top., with aluminum cap marked:

SC	
T1N R4W	
S31	S32
<hr/>	
1997	

Deposit the marked stone and galvanized post alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, North of corner.

INVESTIGATIONAL RETRACEMENT SURVEY AND DEPENDENT RESURVEY  
FOR THE SOUTH BOUNDARY, (UINTAH SPECIAL BASE LINE),  
T. 1 N., R. 4 W., UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

S. 89° 34.2' W., on the South boundary of section 31, for T. 1 N., R. 4 W., along the true Latitudinal curve line between controlling corners.

20.032

The standard East 1/16 section corner of section 31 only, on the South boundary of the Township, monumented with a Sandstone, 8 x 5 x 5 ins. above ground, plainly marked 1/16 on the North face, with a galvanized post 2 1/2 ins. diam., cap marked 1/16 SC S 31 1959, and a mound of stone to the North. (Record: Sandstone 13 x 12 x 9 ins., marked SC 1/16 on East face, encircled by a mound of earth 3 ft. diam. at base and 1 ft. high ).

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

SC  
T1N R4W  
E 1/16 S 31  
-----  
1997

Deposit the marked stone and galvanized post alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, North of corner.

S. 89° 53.6' W., beginning new measurement, on the South boundary of section 31, for T. 1 N., R. 4 W., along the true Latitudinal curve line between controlling corners.

20.057

Point for the standard 1/4 section corner of section 31 only, on the South boundary of the Township, at proportionate dist.; there is no remaining evidence of the original corner. (Record: Sandstone 12 x 12 x 4 ins., marked SC 1/4 on East face, encircled by a mound of earth 3 ft. diam. at base and 1 ft. high ).

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 24 ins. in the ground, with aluminum cap marked:

SC  
T1N R4W  
1/4 S 31  
-----  
1997

Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, North of corner.

Found a galvanized pipe, 30 ins. long, 2 1/2 ins. diam., laying loose, near point.

Deposit galvanized pipe alongside aluminum post.

INVESTIGATIONAL RETRACEMENT SURVEY AND DEPENDENT RESURVEY  
FOR THE SOUTH BOUNDARY, (UINTAH SPECIAL BASE LINE),  
T. 1 N., R. 4 W., UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

40.114

The standard West 1/16 section corner of section 31 only, on the South boundary of the Township, monumented with a Sandstone, 10 x 7 x 5 ins. above ground, plainly marked 1/16 on North face, with a galvanized post, 2 1/2 ins. diam., cap marked SC 1/16 S 31 1959. (Record: Sandstone 18 x 14 x 9 ins., marked SC 1/16 on East face, encircled by a mound of earth and stone 3 ft. diam. at base and 1 ft. high ).

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 24 ins. in the ground, with aluminum cap marked:

SC
W 1/16 S 31
-----
1997

Deposit the marked stone and galvanized post alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, North of corner.

S. 89° 41.1' W., beginning new measurement on the South boundary of section 31, for T. 1 N., R. 4 W., along the true Latitudinal curve line between controlling corners.

8.002

The closing corner of sections 1 and 6, T. 1 S., Rs. 4 and 5, W., monumented with a Sandstone, 12 x 10 x 6 ins. above ground, plainly marked 6 grooves on the South face, with a mound of stone to the South. Also a galvanized post, 2 1/2 ins. diam., marked CC 1-6 1959, alongside. (Record: Sandstone 12 x 12 x 12 ins. marked CC T1S on South face, R4E on East face, R5W on West face, along with 6 grooves on South, East and West, encircled by a mound of stone 3 ft. diam. at base and 2 ft. high. )

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 24 ins. in the ground,, with aluminum cap marked:

T1N R4W
S 31
-----
S1   S6
C C
R5W R4W
T1S
1997

Deposit the marked stone and galvanized post alongside the aluminum post.



INVESTIGATIONAL RETRACEMENT SURVEY, AND DEPENDENT RESURVEY  
FOR A PORTION OF THE EAST BOUNDARY,  
T. 1 N., R. 4 W., UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

19.650

Rebuild mound of stone, with 3 ft. base, 2 ft. high, South of corner.

The standard corner of Tps. 1 N., Rs. 4 W. and 5 W., monumented with a Sandstone 16 x 12 x 12 ins. above ground, plainly marked 6 grooves on the East face and 6 grooves on the West face and an SC on the North face. Also a galvanized post 2 1/2 ins. diam., projecting 16 ins. above ground is alongside Sandstone. Post was set by B.I.A. in 1959. ( Record: Sandstone 18 x 15 x 10 ins., marked SC with 6 grooves on North face and 6 grooves on East and West face, encircled by a mound of stone 3 ft. diam. at base 1 ft. high ).

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, with aluminum cap marked:

SC	
T1N	
R5W	R4W
S36	S31
1997	

Deposit the marked stone and galvanized post alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, North of corner.

The geographic position of the Southwest township corner on the Uintah Special Base Line as determined by Global Positioning System, is as follows:

Latitude 40° 25' 53.4289" N.      Longitude 110° 23' 28.6742" W.  
N.A.D. 1983 ( 1994 )

---

Investigational Retracement Survey, and Dependent Resurvey  
For a Portion of the East boundary,  
Township 1 North, Range 4 West, Uintah Special Meridian, Utah

---

Reestablishment of the Survey & Resurvey Executed by:  
D.G. Major in 1882, & H.D. Heist in 1904.

---

From the South-East standard township corner of T. 1 N., R. 4 W., heretofore described.

N. 0° 07.8' W., on the East boundary of section 36, T. 1 N., R. 4 W.

Asc. Gradual South slope along fence line.

INVESTIGATIONAL RETRACEMENT SURVEY, AND DEPENDENT RESURVEY  
FOR A PORTION OF THE EAST BOUNDARY,  
T. 1 N., R. 4 W., UINTAH SPECIAL MERIDIAN, UTAH

**CHAINS****6.040**

The closing corner of sections 6 and 31, Tps. 1 N. & 1 S., R. 3 W., on the East boundary of the Township, monumented with an aluminum post, 2 1/2 ins. diam. firmly set and projecting 2 ins. above a mound of stone, with aluminum cap marked as described in the concurrent Group 800 of the resurvey of the West boundary of T. 1 S., R. 3 W. (Record: 1903 Trachyte stone 20 x 12 x 8 ins., projecting 5 ins. above ground marked CC on East face with 6 grooves on North, South, and East faces.)

**19.809**

Point for the South 1/16 section corner of section 36 only, on the East boundary of the Township, at proportionate distance; ( 1882 Record: Sandstone 16 x 10 x 7 ins., marked 1/16 on North face, encircled by a mound of earth 3 ft. diam. at base and 2 ft. high ). ( 1903 Record Sandstone 10 x 7 x 6 ins. above ground, marked as described in the 1882 survey )

**NOTE:** Corner not monumented, due to no verification of ground evidence was perform.

**39.618**

The 1/4 section corner of section 36 only, on the East boundary of the Township, monumented with a Sandstone 12 x 9 x 5 ins., firmly set, projecting 2 ins. above ground, plainly marked 1/4 on the West face. ( 1882 Record: Sandstone 10 x 10 x 8 ins. marked 1/4 on North face, encircled by a mound of earth 3 ft. diam. at base and 2 ft. high ). ( 1903 Record: Sandstone 10 x 8 x 4 ins. above ground, marked as described in the 1882 survey. )

From which the original bearing trees:

A fallen dead pinon, 14 ins. diam., bears S. 26° E., 68 links dist.,  
plainly marked 1/4 S 36 BT. ( 1903 Record: Pinon, 10 ins. diam.,  
bears S. 26° E., 68 links dist. )

A juniper, 12 ins. diam., bears S. 24° W., 31 links dist.,  
marked 1/4 S 36 BT. ( 1903 Record: Pinon, 10 ins., bears S. 34° W.,  
30 links dist. )

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 24 ins. in the ground, with aluminum cap marked:

T1N	
R4W	
1/4	
S36	
1995	

Deposit the marked stone alongside the aluminum post.

---

N. 0° 32.6' E., on the East boundary of section 36 only, T.1 N., R. 4 W.

**19.980**

Point for the North 1/16 section corner of section 36 only, on the East boundary of the Township, at proportionate distance; ( 1882 Record: Sandstone 11 x 11 x 9 ins., marked 1/16 on North face, encircled by a mound of earth 3 ft. diam. at base and 2 ft. high ). ( 1903 Record: Sandstone 12 x 8 x 6 ins. marked 1/16 on West face, raise a mound of stone 2 ft. at base, 1 1/2 ft. high, West of corner.

**INVESTIGATIONAL RETRACEMENT SURVEY, AND DEPENDENT RESURVEY  
FOR A PORTION OF THE EAST BOUNDARY,  
T. 1 N., R. 4 W., UTAH SPECIAL MERIDIAN, UTAH**

**CHAINS**

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

**39.960**

The corner of sections. 25 and 36, on the East boundary of the township, monumented with a Trachyte stone, 18 x 12 x 8 ins., projecting 8 ins. above ground with 1 notch on South edge and 5 notches on the North edge, encircled by a scatter mound of stone. ( 1882 Record: Sandstone 13 x 13 x 4 ins., marked with 5 grooves on the North face and 6 grooves on the East face, encircled by a mound of earth 3 ft. diam.at base and 2 ft high ). ( 1903 Record Trachyte stone 18 x 12 x 8 ins. above ground with 1 notch on South edge and 5 notches on North edge. raise a mound of stone 2 ft. At base, 1 1/2 ft. high, West of corner. )

At the corner point

Set an iron post, 30 ins. long, 2 1/2 ins. diameter, 24 ins. in the ground, with brass cap mkd.

T	1	N
R	4	W
S	25	

S	36
1995	

Deposit the marked stone alongside the iron post.

---

**N. 0° 19' E.,** on the East boundary of section 25 only, T. 1 N., R. 4 W.

**20.147**

Point for the South 1/16 section corner of section 25 only, on the East boundary of the Township, at proportionate distance; ( 1882 Record: Sandstone 14 x 10 x 5 ins., marked 1/16 on North face, encircled by a mound of earth 3 ft. diam.at base and 2 ft. high ). ( 1903 Record: Sandstone 12 x 8 x 8 ins. above ground, marked 1/16 on West face, encircled with a mound of stone 2 ft. at base, 1 1/2 ft. high ).

**NOTE:** Corner not monumented, no verification of ground evidence was perform.

**40.293**

The 1/4 section corner of section 25 only, on the East boundary of the Township, monumented with a Trachyte stone 16 x 10 x 6 ins., firmly set, projecting 6 ins. above ground, marked 1/4 on the West face. ( 1882 Record: Sandstone 23 x 14 x 4 ins. marked 1/4 on North face, encircled by a mound of earth 3 ft. diam. at base and 2 ft. high ). ( 1903 Record: Trachyte stone 16 x 10 x 6 ins. above ground, marked 1/4 on West face encircled by a mound 2 ft. at base, 1 1/2 ft. high. )

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 24 ins. in the ground, with aluminum cap marked:

T1N
R4W
1/4
S25
1995

INVESTIGATIONAL RETRACEMENT SURVEY, AND DEPENDENT RESURVEY  
FOR A PORTION OF THE EAST BOUNDARY,  
T. 1 N., R. 4 W., UINTAH SPECIAL MERIDIAN, UTAH

## CHAINS

Deposit the marked stone alongside the aluminum post.

N. 0° 20.6' E., on the East boundary of section 25, T.1 N., R. 4 W.

20.082

Point for the North 1/16 section corner of section 25 only, on the East boundary of the Township, at proportionate distance; ( 1882 Record: Sandstone 20 x 12 x 6 ins., marked 1/16 on North face, encircled by a mound of earth 3 ft. diam.at base and 2 ft. high ). ( 1903 Record: Trachyte stone 12 x 8 x 8 ins. above ground, marked 1/16 on West face, encircled by a mound of stone 2 ft. base, 1 1/2 ft. high.

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

40.164

The corner of sections 24 and 25, on the East boundary of the Township, monumented with a Trachyte stone, 18 x 10 x 8 ins. Projecting 6 ins. above ground with 2 notch on South edge and 4 notches on the North edge encircled by a scatter mound of stone. ( 1882 Record: Sandstone 17 x 10 x 7 ins., marked with 4 grooves on the North face and 6 grooves on the East face, encircled by a mound of earth 3 ft. diam.at base and 2 ft high ). ( 1903 Record: Trachyte stone 18 x 10 x 8 ins. above ground, marked with 2 notches on South and 4 notches on North edges, mound of stone 2 ft. at base, 1 1/2 ft. high, West of corner ).

At the corner point

Set an iron post, 30 ins. long, 2 1/2 ins. diameter, 24 ins. in the ground, with brass cap mkd.

T 1 N	
R 4 W	
<u>S 24</u>	
S 25	
1995	

Deposit the marked stone alongside the iron post.

From this corner, the Altonah Azimuth mark, bears N. 45° 29' 24" W., for 63.789 chains distance, hereinafter described in the General Description.

Investigational Retracement Survey,  
For a Portion of the East boundary,  
Township 1 North, Range 4 West, Uintah Special Meridian, Utah

Investigational Retracement Survey for the Survey & Resurvey Executed by:  
D.G. Major in 1882, & H.D. Heist in 1903.

From the corner of sections. 24 and 25, on the East boundary of the Township, heretofore described

N. 0° 22.1' E., on the East boundary of section 24, T. 1 N., R. 4 W.

INVESTIGATIONAL RETRACEMENT SURVEY, AND DEPENDENT RESURVEY  
FOR A PORTION OF THE EAST BOUNDARY,  
T. 1 N., R. 4 W., UINTAH SPECIAL MERIDIAN, UTAH

**CHAINS****20.099**

Point for the South 1/16 section corner of section 24 only, on the East boundary of the Township, at proportionate distance; ( 1882 Record: Sandstone 16 x 10 x 7 ins., marked 1/16 on North face, encircled by a mound of earth 3 ft. diam. at base and 2 ft. high ). ( 1903 Record: Trachyte stone 13 x 8 x 8 ins. above ground, marked 1/16 on West face, a mound of stone 2 ft. at base, 1 1/2 ft. High, West of corner.

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

**40.198**

Point for 1/4 section corner of section 24 only, on the East boundary of the Township, at proportionate distance; ( Record: Sandstone 12 x 12 x 7 ins. marked 1/4 on North face, encircled by a mound of earth 3 ft. diam. at base and 2 ft. high ). ( 1903 Record: Trachyte stone 16 x 10 x 8 ins. above ground, marked 1/4 on West face, a mound of stone 2 ft. at base, 1 1/2 ft. high, West of corner.

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

**60.296**

Point for the North 1/16 section corner of section 24 only, on the East boundary of the Township, at proportionate distance; ( 1882 Record: Sandstone 15 x 12 x 4 ins., marked 1/16 on North face, encircled by a mound of earth 3 ft. diam. at base and 2 ft. high ). ( 1903 Record: Trachyte Stone 12 x 8 x 7 ins. above ground, marked 1/16 on West face, encircled by a mound of stone 2 ft. at base 1 1/2 ft. high.

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

**80.395**

The corner of sections. 13 and 24, on the East boundary of the Township, monumented with a Sandstone, 10 x 6 x 4 ins. Projecting 5 ins. above ground with 3 notches on South edge and 3 notches on the North edge encircled by a scatter mound of stone. ( 1882 Record: Sandstone 14 x 10 x 16 ins., marked with 3 grooves on the North face and 6 grooves on the East face, encircled by a mound of earth 3 ft. diam. at base and 2 ft high ). ( 1903 Record: Sandstone 10 x 6 x 4 ins. above ground, marked as described in the 1882 survey )

**NOTE:** No further restoration was perform due to funding restraints.

---

From the corner of sections. 13 and 24, on the East boundary of the Township, heretofore described

N. 0° 00.7' W., on the East boundary of section 13, T. 1 N., R. 4 W.

**19.989**

Point for the South 1/16 section corner of section 13 only, on the East boundary of the Township, at proportionate distance; ( 1882 Record: Sandstone 22 x 18 x 12 ins., marked 1/16 on North face, encircled by a mound of earth 3 ft. diam., at base and 2 ft. high ). ( 1903 Record: Sandstone 18 x 12 x 6 ins. above ground, marked as described in the 1882 survey. )

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

**39.977**

Point for 1/4 section corner of section 13 only, on the East boundary of the Township, at proportionate distance; ( 1882 Record: Sandstone 20 x 15 x 6 ins. marked 1/4 on North face, encircled by a mound of earth 3 ft. diam. at base and 2 ft. high ). ( 1903 Record: Sandstone 15 x 6 x 5 ins above ground, marked as described in the 1882 survey. )

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

INVESTIGATIONAL RETRACEMENT SURVEY, AND DEPENDENT RESURVEY  
FOR A PORTION OF THE EAST BOUNDARY,  
T. 1 N., R. 4 W., UINTAH SPECIAL MERIDIAN, UTAH

**CHAINS****59.966**

Point for the North 1/16 section corner of section 13 only, on the East boundary of the Township, at proportionate distance; ( 1882 Record: Sandstone 18 x 10 x 5 ins., marked 1/16 on North face, encircled by a mound of earth 3 ft. diam.at base and 2 ft. high ). ( 1903 Record: Sandstone 10 x 5 x 5 ins. above ground, marked as described in the 1882 survey )

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

**79.954**

The corner of sections. 12 and 13, on the East boundary of the Township, monumented with a Sandstone, 10 x 6 x 4 ins. Projecting 5 ins. above ground with 3 notches on South edge and 3 notches on the North edge encircled by a scatter mound of stone. ( 1882 Record: Sandstone 25 x 12 x 7 ins., marked with 2 grooves on the North face and 6 grooves on the East face, encircled by a mound of earth 3 ft. diam.at base and 2 ft high ). ( 1903 Record: Sandstone 12 x 10 x 7 ins. above ground marked as described in the 1882 survey. )

**NOTE:** No further restoration was perform due to funding restraints.

---

From the corner of sections. 12 and 13, on the East boundary of the Township, heretofore described

**North**, on the East boundary of section 12 only, T. 1 N., R. 4 W.

**19.905**

Point for the South 1/16 section corner of section 12 only, on the East boundary of the Township, at proportionate distance; ( 1882 Record: Sandstone 15 x 12 x 7 ins., marked 1/16 on North face, encircled by a mound of earth 3 ft. diam.at base and 2 ft. high ). ( 1903 Record: Sandstone 12 x 7 x 5 ins above ground, marked as described in the 1882 survey )

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

**39.809**

Point for 1/4 section corner of section 12 only, on the East boundary of the Township, at proportionate distance; ( 1882 Record: Sandstone 16 x 12 x 7 ins. marked 1/4 on North face, encircled by a mound of earth 3 ft. diam. at base and 2 ft. high ). ( 1903 Record: Sandstone 12 x 7 x 6 ins. above ground, marked 1/4 on West face, mound of stone 2 ft. at base 1 1/2 ft. high, West of corner. )

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

**59.714**

Point for the North 1/16 section corner of section 12 only, on the East boundary of the Township, at proportionate distance; ( 1882 Record: Sandstone 21 x 12 x 8 ins., marked 1/16 on North face, encircled by a mound of earth 3 ft. diam.at base and 2 ft. high ). ( 1903 Record: Sandstone 12 x 8 x 8 ins. above ground, marked as described in the 1882 survey. )

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

**79.618**

The corner of sections. 1 and 12, on the East boundary of the Township, monumented with a Sandstone, 10 x 6 x 4 ins. Projecting 5 ins. above ground with 3 notches on South edge and 3 notches on the North edge encircled by a scatter mound of stone. ( 1882 Record: Sandstone 25 x 9 x 9 ins., marked with 1 groove on the North face and 6 grooves on the East face, encircled by a mound of earth 3 ft. diam.at base and 2 ft high ). ( 1903 Record: Sandstone 10 x 10 x 7 ins above ground, marked with 5 notches on South and 1 notch on the North, mound of stone to the West. )

**NOTE:** No further restoration was performed due to funding restraints.

---

INVESTIGATIONAL RETRACEMENT SURVEY, AND DEPENDENT RESURVEY  
FOR A PORTION OF THE EAST BOUNDARY,  
T. 1 N., R. 4 W., UTAH SPECIAL MERIDIAN, UTAH

**CHAINS**

From the corner of sections. 1 and 12, on the East boundary of the Township, heretofore described

N. 0° 00.4' W., on the East boundary of section 1 only, T. 1 N., R. 4 W.

**20.00**

Point for the South 1/16 section corner of section 1 only, on the East boundary of the Township, at proportionate distance; ( 1882 Record: Sandstone 18 x 16 x 12 ins., marked 1/16 on North face, encircled by a mound of earth 3 ft. diam. at base and 2 ft. high ). ( 1903 Record: Sandstone 12 x 10 x 6 ins above ground, marked as described in the 1882 survey. )

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

**40.00**

Point for 1/4 section corner of section 1 only, on the East boundary of the Township, at proportionate distance; ( 1882 Record: Sandstone 16 x 13 x 9 ins. marked 1/4 on North face, encircled by a mound of earth 3 ft. diam. at base and 2 ft. high ). ( 1903 Record: Sandstone 13 x 9 x 6 ins above ground, marked as described in the 1882 survey. )

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

**60.00**

Point for the North 1/16 section corner of section 1 only, on the East boundary of the Township, at proportionate distance; ( 1882 Record: Sandstone 17 x 11 x 6 ins., marked 1/16 on North face, encircled by a mound of earth 3 ft. diam. at base and 2 ft. high ). ( 1903 Record: Sandstone 11 x 6 x 6 ins. above ground, marked as described in the 1882 survey. )

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

**80.00**

The corner of sections. 1 and 36, at the North-East Standard Township Corner of T.1N., R. 4 W., monumented with a Sandstone, 10 x 6 x 4 ins. Projecting 5 ins. above ground with 3 notch on South edge and 3 notches on the North edge encircled by a scatter mound of stone. ( 1882 Record: Sandstone 20 x 10 x 5 ins., marked with 6 grooves on the North, East, South, and West face, encircled by a mound of earth 3 ft. diam. at base and 1 1/2 ft high ). ( 1903 Record: Sandstone 12 x 10 x 5 ins. above ground, marked as described in the 1882 survey. )

**NOTE:** No further restoration was perform due to funding restraints.

From this point the 1903 Closing Corner for T. 1 & 2 N., R.3 W., bears. N. 0° 00.4 W., 4.608 chains distance, monumented with a Trachyte Stone 20 x 12 x 8 ins. above ground, marked CC on East face with 6 grooves on North, South, and East face.

From this point the North-West Township corner of T.1 N., R. 4 W., bears S. 89° 53.5' W., on a forward bearing, 478.848 chains distance, hereinafter described within these field notes as pertaining to the West boundary

---

Investigational Retracement Survey,  
For the West Boundary,  
Township 1 North, Range 4 West, Uintah Special Meridian, Utah

---

Investigational Retracement Survey for the Survey Executed by:  
D.G. Major in 1882,

---

INVESTIGATIONAL RETRACEMENT SURVEY FOR THE WEST BOUNDARY,  
T. 1 N., R. 4 W., UTAH SPECIAL MERIDIAN, UTAH

**CHAINS**

From the South-West standard township corner of T. 1 N., R. 4 W., heretofore described.

N. 0° 10' E., on the West boundary of section 31 only, T. 1 N., R. 4 W.

**23.024** Point for the South 1/16 section corner of section 31 only, on the West boundary of the Township, at proportionate distance. ( Record: Sandstone 15 x 12 x 7 ins., marked 1/16 on North face, encircled by a mound of earth 3 ft. diam. at base and 2 ft. high ).

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

**40.048** Point for the 1/4 section corner of section 31 only, on the West boundary of the Township, at proportionate distance, there is no remaining evidence of the original corner. ( Record: Sandstone 14 x 14 x 6 ins. marked 1/4 on North face, encircled by a mound of earth 3 ft. diam. base and 1 ft. high ).

**NOTE:** Corner not monumented, due to funding restraints.

**60.072** Point for the North 1/16 section corner of section 31 only, on the West boundary of the township, at proportionate distance. ( Record: Sandstone 18 x 10 x 6 ins., marked 1/16 on North face, encircled by a mound of earth 3 ft. diam. at base and 1 ft. high ).

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

**80.096** The corner of sections, 30, and 31 only, on the West boundary of the Township, at proportionate distance, there is no remaining evidence of the original corner. ( Record: Sandstone 15 x 11 x 6 ins., marked with 5 grooves on the North face and 6 grooves on the East face, encircled by a mound of earth 3 ft. diam. at base and 1 ft high ).

**NOTE:** Corner not monumented, due to funding restraints.

---

N. 0° 10' E., on the West boundary of section 30 only, T. 1 N., R. 4 W.

**20.024** Point for the South 1/16 section corner of section 30 only, on the West boundary of the Township, at proportionate distance. ( Record: Sandstone 17 x 15 x 9 ins., marked 1/16 on North face, encircled by a mound of stone 3 ft. diam. at base and 1 ft. high ).

**NOTE:** Corner not monument due to no verification of ground evidence was performed.

**40.048** Point for the 1/4 section corner of section 30 only, on the West boundary of the Township, at proportionate distance, there is no remaining evidence of the original corner. ( Record: Sandstone 18 x 13 x 4 ins. marked 1/4 on North face, encircled by a mound of stone 3 ft. diam. at base and 1 ft. high ).

**NOTE:** Corner not monument, due to funding restraints.

**60.072** Point for the North 1/16 section corner of section 30 only, on the West boundary of the Township, at proportionate distance. ( Record: Sandstone 17 x 14 x 6 ins., marked 1/16 on North face, encircled by a mound of stone 3 ft. diam. at base and 1 ft. high ).

**NOTE:** Corner not monumented, no verification of ground evidence was performed.



INVESTIGATIONAL RETRACEMENT SURVEY FOR THE WEST BOUNDARY,  
T. 1 N., R. 4 W., UTAH SPECIAL MERIDIAN, UTAH

**CHAINS****80.096**

The corner of sections 19, and 30 only, on the West boundary of the Township, at proportionate distance, there is no remaining evidence of the original corner. ( Record: Sandstone 21 x 13 x 7 ins., marked with 4 grooves on the North face and 6 grooves on the East face, encircled by a mound of stone 3 ft. diam.at base and 1 ft high ).

**NOTE:** Corner not monumented, due to funding restraints.

From the corner of sections. 19 and 30, on the West boundary of the Township, heretofore described

N. 0° 10' E., on the West boundary of section 19 only, T. 1 N., R. 4 W.

**20.024**

Point for the South 1/16 section corner of section 19 only, on the West boundary of the Township, at proportionate distance, ( Record: Sandstone 14 x 12 x 4 ins., marked 1/16 on North face, encircled by a mound of stone 3 ft. diam.at base and 1 ft. high ).

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

**40.048**

Point for 1/4 section corner of sections 19 only, on the West boundary of the Township, at proportionate distance. ( Record: Sandstone 13 x 12 x 5 ins. marked 1/4 on North face, encircled by a mound of earth 3 ft. diam. at base and 1 ft. high ).

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

**60.072**

Point for the North 1/16 section corner of sections 19 only, on the West boundary of the Township, at proportionate distance. ( Record: Sandstone 16 x 15 x 4 ins., marked 1/16 on North face, encircled by a mound of stone 3 ft. diam.at base and 1 ft. high ).

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

**80.096**

The corner of sections 18, and 19 only, on the West boundary of the Township, at proportionate distance. ( Record: Sandstone 15 x 14 x 5 ins., marked with 3 grooves on the North face and 6 grooves on the East face, encircled by a mound of stone 3 ft. diam.at base and 1 ft high ).

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

From the corner of sections 18, and 19 only, on the West boundary of the Township, heretofore described

N. 0° 10' E., on the West boundary of section 18 only, T. 1 N., R. 4 W.

**20.024**

Point for the South 1/16 section corner of section 18 only, on West boundary of the Township, at proportionate distance, falls in West Branch of Lake Fork River. ( Record: Sandstone 18 x 10 x 5 ins., marked 1/16 on North face, encircled by a mound of earth 3 ft. diam.at base and 1 ft. high ).

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

**40.048**

Point for 1/4 section corner of section 18 only, on the West boundary of the Township, at proportionate distance. ( Record: Sandstone 19 x 16 x 4 ins. marked 1/4 on North face, encircled by a mound of stone 3 ft. diam. at base and 1 ft. high ).

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

**INVESTIGATIONAL RETRACEMENT SURVEY FOR THE WEST BOUNDARY,  
T. 1 N., R. 4 W., UINTAH SPECIAL MERIDIAN, UTAH**

**CHAINS****60.072**

Point for the North 1/16 section corner of section 18 only, on the West boundary of the Township, at proportionate distance, falls in West Branch of Lake Fork River, course South-East, 100 links wide. ( Record: Sandstone 16 x 10 x 7 ins., marked 1/16 on North face, encircled by a mound of earth 3 ft. diam.at base and 2 ft. high ).

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

**80.096**

The corner of sections. 7, and 18 only, on the West boundary of the Township, at proportionate distance. ( Record: Sandstone 17 x 12 x 5 ins., marked with 2 grooves on the North face and 6 grooves on the East face, encircled by a mound of stone 3 ft. diam.at base and 1 ft high ).

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

---

From the corner of sections. 7, and 18 only, on the West boundary of the Township, heretofore described

**N. 0° 10' E.,** on the West boundary of section 7 only, T 1 N., R. 4 W.

**20.024**

Point for the South 1/16 section corner of section 7 only, on the West boundary of the Township, at proportionate distance. ( Record: Sandstone 10 x 10 x 5 ins., marked 1/16 on North face, encircled by a mound of earth 3 ft. diam.at base and 1 ft. high ).

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

**40.048**

Point for 1/4 section corner of sections 7 only, on the West boundary of the Township, at proportionate distance. ( Record: Sandstone 16 x 9 x 7 ins. marked 1/4 on North face, encircled by a mound of earth 3 ft. diam. at base and 1 ft. high ).

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

**60.072**

Point for the North 1/16 section corner of section 7 only, on the West boundary of the Township, at proportionate distance. ( Record: Sandstone 15 x 12 x 10 ins., marked 1/16 on North face, encircled by a mound of earth 3 ft. diam.at base and 1 ft. high ).

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

**80.096**

The corner of sections 6, and 7 only, on the West boundary of the Township, at proportionate distance. ( Record: Sandstone 17 x 15 x 6 ins., marked with 1 groove on the North face and 6 grooves on the East face, encircled by a mound of stone 3 ft. diam.at base and 1 ft high ).

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

---

From the corner of sections 6, and 7 only, on the West boundary of the Township, heretofore described

**N. 0° 10' E.,** on the West boundary of section 6 only, T 1 N., R. 4 W.

**20.024**

Point for the South 1/16 section corner of section 6 only, on the West boundary of the Township, at proportionate distance. ( Record: Sandstone 15 x 12 x 5 ins., marked 1/16 on North face, encircled by a mound of stone 3 ft. diam.at base and 1 ft. high ).

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

**INVESTIGATIONAL RETRACEMENT SURVEY FOR THE WEST BOUNDARY,  
T. 1 N., R. 4 W., UINTAH SPECIAL MERIDIAN, UTAH**

**CHAINS****40.048**

Point for 1/4 section corner of section 6 only, on the West boundary of the Township, at proportionate distance. ( Record: Sandstone 23 x 14 x 10 ins. marked 1/4 on North face, encircled by a mound of stone 3 ft. diam. at base and 1 ft. high ).

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

**60.072**

Point for the North 1/16 section corner of section 6 only, on the West boundary of the Township, at proportionate distance; ( Record: Sandstone 19 x 15 x 3 ins., marked 1/16 on North face, encircled by a mound of stone 3 ft. diam. at base and 1 ft. high ).

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

**80.096**

The corner of sections. 1, 6, 31, and 36, at the North-West corner of the Township, monumented with a Sandstone, 22 x 15 x 4 ins. Projecting 5 ins. above ground, marked with 6 notches on North. South, East and West edges, encircled by a scatter mound of stone 3 ft. diam. At base and 1 ft. high. ( Record: Sandstone 22 x 15 x 4 ins., marked with 6 notches on the North, South, East, and West edges, encircled by a mound of stone 3 ft. diam. at base and 1 ft. high ).

from which

A pine 15 ins. diam. bears S. 30° 40' E., 92 links dist.

A pine 12 ins. diam. bears S. 31° 15' W., 30 links dist.

A pine 15 ins. diam. bears N. 15° 00' W., 54 links dist.

**NOTE:** No further restoration was perform due to funding restraints.

From this point the North-East Township corner bears N. 89° 49.1' E., on a forward bearing 478.848 chains distance, heretofore described within these field notes as pertaining to the East boundary .

---

Investigational Retracement Survey  
For the First Latitudinal Section Line,  
Township 1 North, Range 4 West, Uintah Special Meridian, Utah

---

Investigational Retracement Survey,  
For the Survey Executed by D.G. Major in 1882

---

From the corner of sections. 25 and 36 on the East boundary of the Township, heretofore described.

**S. 89° 50.9 W.,** along the First Latitudinal Section Line, on a true latitudinal curve line between sections 25, and 36.

**20.043**

Point for the East 1/16 section corner of sections 25, and 36, at proportionate distance; ( Record: Sandstone 10 x 10 x 8 ins., marked 1/16 on East face, encircled by a mound of earth 2 ft. diam. at base and 1 1/2 ft. high ).

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

INVESTIGATIONAL RETRACEMENT SURVEY FOR THE  
FIRST LATITUDINAL SECTION LINE,  
T. 1 N., R. 4 W., UTAH SPECIAL MERIDIAN, UTAH

**CHAINS****40.086**

Point for the 1/4 section corner of sections 25 and 36, at proportionate distance; there is no remaining evidence of the original corner. ( Record: Sandstone 15 x 10 x 8 ins. marked 1/4 on East face, encircled by a mound of earth 1 1/2 ft. diam. at base and 1 ft. high ).

**NOTE:** Corner not monumented, due to funding restraints.

**60.129**

Point for the West 1/16 section corner of sections 25 and 36, at proportionate distance; ( Record: Sandstone 15 x 10 x 6 ins., marked 1/16 on East face, encircled by a mound of earth 2 ft. diam. at base and 1 1/2 ft. high ).

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

**80.172**

The corner of sections. 25, 26, 35, and 36, at single proportionate distance East and West; there is no remaining evidence of the original corner. ( Record: Sandstone 15 x 10 x 10 ins., marked with 5 grooves on the North face and 1 groove on the East face, encircled by a mound of earth 3 ft. diam. at base and 2 ft high ).

**NOTE:** Corner not monumented, due to funding restraints.

---

From the corner of the sections of 25, 26, 35, and 36.

**S. 89° 50.9 W.**, along the First Latitudinal Section Line, on a true latitudinal curve line between sections 26 and 35.

**19.983**

Point for the East 1/16 section corner of sections 26 and 35, at proportionate distance; ( Record: Sandstone 12 x 11 x 8 ins., marked 1/16 on East face, encircled by a mound of earth 2 ft. diam. at base and 1 ft. high ).

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

**39.966**

Point for the 1/4 section corner of sections 26 and 35, at proportionate distance; there is no remaining evidence of the original corner. ( Record: Sandstone 16 x 10 x 6 ins. marked 1/4 on East face, encircled by a mound of earth 2 ft. diam. at base and 1 1/2 ft. high ).

**NOTE:** Corner not monumented, due to funding restraints.

**59.949**

Point for the West 1/16 section corner of section 26 and 35, at proportionate distance; ( Record: Sandstone 15 x 12 x 7 ins., marked 1/16 on East face, encircled by a mound of earth 2 ft. diam. at base and 1 ft. high ).

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

**79.932**

The corner of sections. 26, 27, 34, and 35, at single proportionate distance East and West; there is no remaining evidence of the original corner. ( Record: Sandstone 18 x 12 x 6 ins., marked with 5 grooves on the North face and 2 grooves on the East face, encircled by a mound of earth 3 ft. diam. at base and 2 1/2 ft high ).

**NOTE:** Corner not monumented, due to funding restraints.

---

From the corner of sections. 26, 27, 34, and 35, heretofore described

**S. 89° 50.9 W.**, along the First Latitudinal Section Line, on a true latitudinal curve line between sections 27 and 34.

INVESTIGATIONAL RETRACEMENT SURVEY FOR THE  
FIRST LATITUDINAL SECTION LINE,  
T. 1 N., R. 4 W., UINTAH SPECIAL MERIDIAN, UTAH

**CHAINS****19.963**

Point for the East 1/16 section corner of section 27 and 34, at proportionate distance; there is no remaining evidence of the original corner. ( Record: Sandstone 10 x 10 x 10 ins., marked 1/16 on East face, encircled by a mound of earth 2 ft. diam.at base and 1 ft. high ).

**NOTE:** Corner not monumented, due to funding restraints.

**39.926**

Point for 1/4 section corner of sections 27 and 34, at proportionate distance; there is no remaining evidence of the original corner. ( Record: Sandstone 13 x 12 x 11 ins. marked 1/4 on East face, encircled by a mound of earth 2 ft. diam. at base and 1 1/2 ft. high ).

**NOTE:** Corner not monumented, due to funding restraints.

**59.889**

Point for the West 1/16 section corner of sections 27 and 34, at proportionate distance; there is no remaining evidence of the original corner. ( Record: Sandstone 12 x 11 x 11 ins., marked 1/16 on East face, encircled by a mound of earth 2 ft. diam.at base and 1 ft. high ).

**NOTE:** Corner not monumented, due to funding restraints..

**79.852**

The corner of sections. 27, 28, 33, and 34, at single proportionate distance East and West; there is no remaining evidence of the original corner. ( Record: Sandstone 16 x 14 x 10 ins., marked with 5 grooves on the North face and 4 grooves on the East face, encircled by a mound of earth 3 ft. diam.at base and 2 1/2 ft. high ).

**NOTE:** Corner not monumented, due to funding restraints.

---

From the corner of sections. 27, 28, 33, and 34, heretofore described.

**S. 89° 50.9 W.,** along the First Latitudinal Section Line, on a true latitudinal curve line between sections 28 and 33.

**19.993**

Point for the East 1/16 section corner of section 28 and 33, at proportionate distance; there is no remaining evidence of the original corner. ( Record: Sandstone 15 x 12 x 6 ins., marked 1/16 on East face, encircled by a mound of earth 2 ft. diam.at base and 1 ft. high ).

**NOTE:** Corner not monumented, due to funding restraints.

**39.986**

Point for 1/4 section corner of section 28 and 33, at proportionate distance; there is no remaining evidence of the original corner. ( Record: Sandstone 20 x 18 x 10 ins. marked 1/4 on East face, encircled by a mound of earth 2 ft. diam. at base and 1 1/2 ft. high ).

**NOTE:** Corner not monumented, due to funding restraints.

**59.979**

Point for the West 1/16 section corner of section 28 and 33, at proportionate distance; there is no remaining evidence of the original corner. ( Record: Sandstone 16 x 12 x 6 ins., marked 1/16 on East face, encircled by a mound of earth 2 ft. diam.at base and 1 ft. high ).

**NOTE:** Corner not monumented, due to funding restraints.

**79.972**

The corner of sections. 28, 29, 32, and 33, at single proportionate distance East and West; there is no remaining evidence of the original corner. ( Record: Sandstone 15 x 10 x 5 ins., marked with 5 grooves on the North face and 4 grooves on the East face, encircled by a mound of earth 3 ft. diam.at base and 2 1/2 ft. high ).

**NOTE:** Corner not monumented, due to funding restraints.

---

INVESTIGATIONAL RETRACEMENT SURVEY FOR THE  
FIRST LATITUDINAL SECTION LINE,  
T. 1 N., R. 4 W., UTAH SPECIAL MERIDIAN, UTAH

**CHAINS**

From the corner of sections. 28, 29, 32, and 33, heretofore described.

**S. 89° 50.9' W.**, along the First Latitudinal Section Line, on a true latitudinal curve line between sections 29 and 32.

- 19.988** Point for the East 1/16 section corner of sections 29, and 32, at proportionate distance; (Record: Sandstone 20 x 10 x 10 ins., marked 1/16 on East face, encircled by a mound of earth 2 ft. diam.at base and 1 ft. high ).

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

- 39.976** Point for 1/4 section corner of sections 29, and 32, at proportionate distance; there is no remaining evidence of the original corner. ( Record: Cottonwood post, 3 1/2 ft. long, 3 1/2 ins. square, marked 1/4 on East face, encircled by a mound of earth 2 1/2 ft. diam. at base and 2 1/2 ft. high ).

**NOTE:** Corner not monumented, due to funding restraints.

- 59.964** Point for the West 1/16 section corner of sections 29, and 32, at proportionate distance; (Record: Cottonwood post 3 ft. long by 3 1/3 ins. square, marked 1/16 on East face, encircled by a mound of earth 2 1/2 ft. diam.at base and 2 1/2 ft. high ).

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

- 79.952** The corner of sections. 29, 30, 31, and 32, at single proportionate distance East and West; there is no remaining evidence of the original corner. ( Record: Sandstone 25 x 15 x 7 ins., marked with 5 grooves on the North face and 5 grooves on the East face, encircled by a mound of earth 3 ft. diam.at base and 2 1/2 ft. high ).

**NOTE:** Corner not monumented, due to funding restraints.

From the corner of sections 29, 30, 31, and 32, heretofore described.

**S. 89° 50.9' W.**, along the First Latitudinal Section Line, on a true latitudinal curve line between 30 and 31.

- 19.953** Point for the East 1/16 section corner of sections 30, and 31, at proportionate distance; (Record: Sandstone 12 x 12 x 5 ins., marked 1/16 on East face, encircled by a mound of earth 2 ft. diam.at base and 1 ft. high ).

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

- 39.906** Point for 1/4 section corner of sections 30, and 31, at proportionate distance; there is no remaining evidence of the original corner. ( Record: Sandstone 13 x 12 x 4 ins. marked 1/4 on East face, encircled by a mound of earth 2 ft. diam. at base and 1 ft. high ).

**NOTE:** Corner not monumented, due to funding restraints.

- 59.859** Point for the West 1/16 section corner of sections. 30, and 31, at proportionate distance; (Record: Sandstone 14 x 11 x 6 ins., marked 1/16 on East face, encircled by a mound of earth 2 ft. diam.at base and 1 ft. high ).

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

INVESTIGATIONAL RETRACEMENT SURVEY FOR THE  
SECOND LATITUDINAL SECTION LINE,  
T. 1 N., R. 4 W., UINTAH SPECIAL MERIDIAN, UTAH

**CHAINS**  
**79.702**

The corner of sections 30 and 31, on the West boundary of the Township, heretofore described.

---

Investigational Retracement Survey  
For the Second Latitudinal Section Line,  
Township 1 North, Range 4 West, Uintah Special Meridian, Utah

---



---

Investigational Retracement Survey  
For the Survey Executed by D.G. Major in 1882

---

From the corner of sections 24 and 25, on the East boundary of the Township, heretofore described.

S. 89° 48.4' W., along the Second Latitudinal Section Line, on a true latitudinal curve line between sections 24 and 25.

**19.903** Point for the East 1/16 section corner of sections 24, and 25, at proportionate distance.; ( Record: Sandstone 12 x 10 x 5 ins., marked 1/16 on East face, encircled by a mound of earth 2 ft. diam.at base and 1 ft. high ).  
**NOTE:** Corner not monumented, no verification of ground evidence was performed.

**39.806** Point for the 1/4 section corner of sections 24 and 25, at proportionate distance.; there is no remaining evidence of the original corner. ( Record: Sandstone 12 x 12 x 6 ins. marked 1/4 on East face, encircled by a mound of earth 2 ft. diam. at base and 1 1/2 ft. high ).  
**NOTE:** Corner not monumented, due to funding restraints.

**59.709** Point for the West 1/16 section corner of sections 24 and 25, at proportionate distance; ( Record: Sandstone 16 x 12 x 10 ins., marked 1/16 on East face, encircled by a mound of earth 2 ft. diam.at base and 1 ft. high ).  
**NOTE:** Corner not monumented, no verification of ground evidence was performed.

**79.612** The corner of sections. 23, 24, 25, and 26, at single proportionate distance East and West; there is no remaining evidence of the original corner. ( Record: Sandstone 36 x 30 x 5 ins., marked with 4 grooves on the North face and 1 groove on the East face, encircled by a mound of earth 3 ft. diam.at base and 1 1/2 ft high ).  
**NOTE:** Corner not monumented, due to funding restraints.

---

From the corner of sections. 23, 24, 25, and 26, heretofore described.

S. 89° 48.4' W., along the Second Latitudinal Section Line, on a true latitudinal curve line between sections 23 and 26.

INVESTIGATIONAL RETRACEMENT SURVEY FOR THE  
SECOND LATITUDINAL SECTION LINE,  
T. 1 N., R. 4 W., UINTAH SPECIAL MERIDIAN, UTAH

**CHAINS****20.023**

Point for the East 1/16 section corner of sections 23 and 26, at proportionate distance;  
( Record: Sandstone 15 x 12 x 3 ins., marked 1/16 on East face, encircled by a mound of earth 2 ft. diam. at base and 1 ft. high ).

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

**40.046**

Point for the 1/4 section corner of sections 23 and 26, at proportionate distance; there is no remaining evidence of the original corner. ( Record: Sandstone 14 x 12 x 6 ins. marked 1/4 on East face, encircled by a mound of earth 2 ft. diam. at base and 1 1/2 ft. high ).

**NOTE:** Corner not monumented, due to funding restraints.

**60.069**

Point for the West 1/16 section corner of section 23 and 26, at proportionate distance;  
( Record: Sandstone 14 x 13 x 5 ins., marked 1/16 on East face, encircled by a mound of earth 2 ft. diam. at base and 1 ft. high ).

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

**80.092**

The corner of sections. 22, 23, 26, and 27, at single proportionate distance East and West; there is no remaining evidence of the original corner. ( Record: Sandstone 36 x 30 x 5 ins., marked with 4 grooves on the North face and 2 grooves on the East face, encircled by a mound of earth 3 ft. diam. at base and 2 1/2 ft. high ).

**NOTE:** Corner not monumented, due to funding restraints.

---

From the corner of sections 22, 23, 26, and 27, heretofore described.

S. 89° 48.4' W., along the Second Latitudinal Section Line, on a true latitudinal curve line between sections 22 and 27.

**20.053**

Point for the East 1/16 section corner of sections 22 and 27, at proportionate distance;  
( Record: Sandstone 20 x 16 x 8 ins., marked 1/16 on East face, encircled by a mound of earth 2 ft. diam. at base and 1 ft. high ).

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

**40.106**

Point for 1/4 section corner of sections 22 and 27, at proportionate distance; there is no remaining evidence of the original corner. ( Record: Sandstone 18 x 8 x 6 ins. marked 1/4 on East face, encircled by a mound of earth 2 ft. diam. at base and 1 ft. high ).

**NOTE:** Corner not monumented, due to funding restraints.

**60.159**

Point for the West 1/16 section corner of sections 22 and 27, at proportionate distance;  
( Record: Sandstone 15 x 10 x 6 ins., marked 1/16 on East face, encircled by a mound of earth 2 ft. diam. at base and 1 ft. high ).

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

**80.212**

The corner of sections. 21, 22, 27, and 28, at single proportionate distance East and West; there is no remaining evidence of the original corner. ( Record: Sandstone 18 x 16 x 10 ins., marked with 4 grooves on the North face and 3 grooves on the East face, encircled by a mound of earth 3 ft. diam. at base and 2 1/2 ft. high ).

**NOTE:** Corner not monumented due to funding restraints.

---



INVESTIGATIONAL RETRACEMENT SURVEY FOR THE  
SECOND LATITUDINAL SECTION LINE,  
T. 1 N., R. 4 W., UINTAH SPECIAL MERIDIAN, UTAH

**CHAINS**

From the corner of sections. 21, 22, 27, and 28, heretofore described.

**S. 89° 48.4' W.**, along the Second Latitudinal Section Line, on a true latitudinal curve line between sections 21 and 28.

- 19.993** Point for the East 1/16 section corner of section 21 and 28, at proportionate distance; ( Record: Sandstone 15 x 10 x 6 ins., marked 1/16 on East face, encircled by a mound of earth 2 ft. diam.at base and 1 ft. high ).  
**NOTE:** Corner not monumented, no verification of ground evidence was performed.
- 39.986** Point for 1/4 section corner of sections 21 and 28, at proportionate distance; there is no remaining evidence of the original corner. ( Record: Sandstone 16 x 14 x 12 ins. marked 1/4 on East face, encircled by a mound of earth 2 ft. diam. at base and 1 1/2 ft. high ).  
**NOTE:** Corner not monumented, due to funding restraints.
- 59.979** Point for the West 1/16 section corner of section 21 and 28, at proportionate distance; ( Record: Sandstone 14 x 12 x 10 ins., marked 1/16 on East face, encircled by a mound of earth 2 ft. diam.at base and 1 ft. high ).  
**NOTE:** Corner not monumented, no verification of ground evidence was performed.
- 79.972** The corner of sections. 20, 21, 28, and 29, at single proportionate distance East and West; there is no remaining evidence of the original corner. ( Record: Sandstone 12 x 10 x 5 ins., marked with 4 grooves on the North face and 4 grooves on the East face, encircled by a mound of earth 3 ft. diam.at base and 2 1/2 ft. high ).  
**NOTE:** Corner not monumented, due to funding restraints.
- 
- From the corner of sections. 20, 21, 28, and 29, heretofore described
- S. 89° 48.4' W.**, along the Second Latitudinal Section Line, on a true latitudinal curve line between sections 20 and 29.
- 20.028** Point for the East 1/16 section corner of sections 20, and 29, at proportionate distance; ( Record: Sandstone 17 x 7 x 7 ins.,marked 1/16 on East face, encircled by a mound of earth 2 ft. diam.at base and 1 ft. high ).  
**NOTE:** Corner not monumented, no verification of ground evidence was performed.
- 40.056** Point for 1/4 section corner of sections 20, and 29, at proportionate distance; there is no remaining evidence of the original corner. ( Record: Sandstone 16 x 16 x 10 ins. marked 1/4 on East face, encircled by a mound of earth 2 ft. diam. at base and 1 1/2 ft. high ).  
**NOTE:** Corner not monumented, due to funding restraints.
- 60.084** Point for the West 1/16 section corner of sections 20, and 29, at proportionate distance; ( Record: Sandstone 20 x 6 x 5 ins., marked 1/16 on East face, encircled by a mound of earth 2 ft. diam.at base and 1 ft. high ).  
**NOTE:** Corner not monumented, no verification of ground evidence was performed.

INVESTIGATIONAL RETRACEMENT SURVEY FOR THE  
SECOND LATITUDINAL SECTION LINE,  
T. 1 N., R. 4 W., UINTAH SPECIAL MERIDIAN, UTAH

**CHAINS**  
**80.112**

The corner of sections. 19, 20, 29, and 30, at single proportionate distance East and West; there is no remaining evidence of the original corner. ( Record: Sandstone 20 x 18 x 10 ins., marked with 4 grooves on the North face and 5 grooves on the East face, encircled by a mound of earth 3 ft. diam.at base and 2 1/2 ft. high ).

**NOTE:** Corner not monumented, due to funding restraints.

From the corner of sections 19, 20, 29, and 30, heretofore described.

**S. 89° 48.4' W.**, along the Second Latitudinal Section Line, on a true latitudinal curve line between sections 20 and 29.

**19.973**

Point for the East 1/16 section corner of sections 19, and 30, at proportionate distance; ( Record: Sandstone 20 x 18 x 8 ins., marked 1/16 on East face, encircled by a mound of earth 2 ft. diam.at base and 1 ft. high ).

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

**39.946**

Point for 1/4 section corner of sections 19, and 30, at proportionate distance; there is no remaining evidence of the original corner. ( Record: Sandstone 12 x 10 x 5 ins. marked 1/4 on East face, encircled by a mound of earth 2 ft. diam. at base and 1 1/2 ft. high ).

**NOTE:** Corner not monumented, due to funding restraints.

**59.919**

Point for the West 1/16 section corner of sections. 19, and 30, at proportionate distance; ( Record: Sandstone 13 x 11 x 8 ins., marked 1/16 on East face, encircled by a mound of earth 2 ft. diam.at base and 1 ft. high ).

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

**79.702**

The corner of sections. 19 and 30, on the West boundary of the township, heretofore described.

---

Investigational Retracement Survey,  
For a Portion of the Subdivisional Section Lines  
Township 1 North, Range 4 West, Uintah Special Meridian, Utah

---



---

Investigational Retracement Survey  
For the Survey Executed by D.G. Major in 1882

---

From the corner of sections 35 and 36, on the South boundary of the Township.

**N. 0° 01.3' W.**, between sections 35 and 36.

**19.916**

Point for the South 1/16 section corner of sections 35, and 36, at proportionate distance; ( Record: Sandstone 16 x 10 x 8 ins., marked 1/16 on North face, encircled by a mound of earth 3 ft. diam.at base and 2 ft. high ).

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

INVESTIGATIONAL RETRACEMENT SURVEY FOR A  
PORTION OF THE SUBDIVISIONAL SECTION LINES,  
T. 1 N., R. 4 W., UTAH SPECIAL MERIDIAN, UTAH

**CHAINS**

- 39.832** Point for 1/4 section corner of sections 35 and 36, at proportionate distance; there is no remaining evidence of the original corner. ( Record: Sandstone 13 x 9 x 8 ins. marked 1/4 on North face, encircled by a mound of earth 3 ft. diam. at base and 2 ft. high ).  
**NOTE:** Corner not monumented, due to funding restraints.
- 59.748** Point for the North 1/16 section corner of sections 35 and 36, at proportionate distance; ( Record: Sandstone 13 x 8 x 7 ins., marked 1/16 on North face, encircled by a mound of earth 3 ft. diam. at base and 2 ft. high ).  
**NOTE:** Corner not monumented, no verification of ground evidence was performed.
- 79.664** The corner of sections. 25, 26, 35, and 36, heretofore described.
- 
- From the corner of sections 25, 26, 35, and 36.
- N. 0° 42.6' E.,** between sections 25 and 26.
- 20.101** Point for the South 1/16 section corner of sections 25 and 26, at proportionate distance; ( Record: Sandstone 15 x 9 x 6 ins., marked 1/16 on North face, encircled by a mound of earth 2 ft. diam. at base and 1 ft. high ).  
**NOTE:** Corner not monumented, no verification of ground evidence was performed.
- 40.201** Point for 1/4 section corner of sections 25 and 26, at proportionate distance; there is no remaining evidence of the original corner. ( Record: Sandstone 16 x 12 x 10 ins. marked 1/4 on North face, encircled by a mound of earth 2 ft. diam. at base and 1 1/2 ft. high ).  
**NOTE:** Corner not monumented, due to funding restraints.
- 60.302** Point for the North 1/16 section corner of sections 25 and 26, at proportionate distance; ( Record: Sandstone 16 x 11 x 7 ins., marked 1/16 on North face, encircled by a mound of earth 2 ft. diam. at base and 1 ft. high ).  
**NOTE:** Corner not monumented, no verification of ground evidence was performed.
- 80.402** The corner of sections. 23, 24, 25, and 26, heretofore described.
- 
- From the corner of sections. 34 and 35, on the South boundary of the Township.
- N. 0° 05.1' W.,** between sections 34 and 35.
- 19.923** Point for the South 1/16 section corner of sections 34 and 35, at proportionate distance; there is no remaining evidence of the original corner. ( Record: Sandstone 18 x 8 x 8 ins., marked 1/16 on North face, encircled by a mound of earth 2 ft. diam. at base and 1 ft. high ).  
**NOTE:** Corner not monumented, due to funding restraints.
- 39.846** Point for 1/4 section corner of sections 34 and 35, at proportionate distance; there is no remaining evidence of the original corner. ( Record: Sandstone 20 x 18 x 3 ins. marked 1/4 on North face, encircled by a mound of earth 2 ft. diam. at base and 1 1/2 ft. high ).  
**NOTE:** Corner not monumented, due to funding restraints.

INVESTIGATIONAL RETRACEMENT SURVEY FOR A  
PORTION OF THE SUBDIVISIONAL LINES,  
T. 1 N., R. 4 W., UTAH SPECIAL MERIDIAN, UTAH

**CHAINS****59.769**

Point for the North 1/16 section corner of sections 34 and 35, at proportionate distance; there is no remaining evidence of the original corner. ( Record: Sandstone 19 x 9 x 8 ins., marked 1/16 on North face, encircled by a mound of earth 2 ft. diam.at base and 1 ft. high ).

**NOTE:** Corner not monumented, due to funding restraints.

**79.692**

The corner of sections 26, 27, 34, and 35, heretofore described.

---

From the corner of sections 26, 27, 34, and 35.

N. 0° 35.0' E., between sections 26 and 27.

**20.085**

Point for the South 1/16 section corner of sections 26 and 27, at proportionate distance; ( Record: Sandstone 16 x 10 x 8 ins., marked 1/16 on North face, encircled by a mound of earth 2 ft. diam.at base and 1 ft. high ).

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

**40.170**

Point for 1/4 section corner of sections 26 and 27, at proportionate distance; there is no remaining evidence of the original corner. ( Record: Sandstone 16 x 10 x 6 ins. marked 1/4 on North face, encircled by a mound of earth 2 ft. diam. at base and 1 1/2 ft. high ).

**NOTE:** Corner not monumented, due to funding restraints.

**60.255**

Point for the North 1/16 section corner of sections 26 and 27, at proportionate distance; ( Record: Sandstone 13 x 9 x 8 ins., marked 1/16 on North face, encircled by a mound of earth 2 ft. diam.at base and 1 ft. high ).

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

**80.340**

The corner of sections 22, 23, 26, and 27, heretofore described.

---

Investigational Retracement Survey and Dependent Resurvey  
For a Portion of the Subdivisional Section Lines,  
Township 1 North, Range 4 West, Uintah Special Meridian, Utah

---

Reestablishment of the Survey Executed by D.G. Major in 1882

---

From the standard corner of section 33 and 34, on the South boundary of the township, hereinbefore described.

N. 0° 03.3' E., between section 33 and 34.

**20.217**

Point for the South 1/16 section corner of section 33 and 34, determined latitudinally by a fence which projects East and West and longitudinally by proportionate distance between controlling corners. There is no remaining evidence of the original monument. ( Record: Sandstone 14 x 10 x 8 ins., marked 1/16 on North face, encircled by a mound of earth 2 ft. diam.at base and 1 ft. high ).

**INVESTIGATIONAL RETRACEMENT SURVEY AND DEPENDENT RESURVEY  
FOR A PORTION OF THE SUBDIVISIONAL LINES,  
T. 1 N., R. 4 W., UTAH SPECIAL MERIDIAN, UTAH**

**CHAINS**

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

S 1/16  
S33 | S34  
1992

Set a steel fence post alongside.

Corner is located 25 links East of a fence which bears North and South.

**40.580**

Point for the 1/4 section corner of sections 33 and 34, determined latitudinally by an old fence line projecting East and West and longitudinally by an old fence line projecting South. This position has long been recognized as the corner by adjacent landowners, and is accepted as the best available evidence of the original corner position. There is no remaining evidence of the original monument. (Record: Sandstone 18 x 8 x 8 ins. marked 1/4 on North face, encircled by a mound of earth 2 ft. diam. at base and 1 ft. high).

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T1N R4W  
1/4  
S33 | S34  
1992

---

Investigational Retracement Survey for Subdivisional Section Lines,  
Township 1 North, Range 4 West, Uintah Special Meridian, Utah

---

Investigational Retracement Survey  
for the Survey Executed by D.G. Major in 1882

---

From the 1/4 section corner of sections 33 and 34.

N. 0° 22.1' E., between section 33 and 34.

**19.573**

Point for the North 1/16 section corner of sections 33 and 34, at proportionate distance; there is no remaining evidence of the original corner. (Record: Sandstone 13 x 10 x 6 ins., marked 1/16 on North face, encircled by a mound of earth 2 ft. diam. at base and 1 ft. high).

**NOTE:** Corner not monumented, due to funding restraints.

**39.146**

The corner of sections 27, 28, 33 and 34, heretofore described.

---

From the corner of sections 27, 28, 33, and 34.

N. 0° 19' E., between sections 27, and 28.

INVESTIGATIONAL RETRACEMENT SURVEY FOR SUBDIVISIONAL SECTION  
LINES, T. 1 N., R. 4 W., UTAH SPECIAL MERIDIAN, UTAH

**CHAINS**

- 20.069** Point for the South 1/16 section corner of sections 27, and 28, at proportionate distance; ( Record: Sandstone 18 x 9 x 6 ins., marked 1/16 on North face, encircled by a mound of earth 2 ft. diam.at base and 1 1/2 ft. high ).  
**NOTE:** Corner not monumented, no verification of ground evidence was performed.
- 40.138** Point for 1/4 section corner of sections 27, and 28, at proportionate distance; there is no remaining evidence of the original corner. ( Record: Sandstone 12 x 8 x 7 ins. marked 1/4 on North face, encircled by a mound of earth 2 ft. diam. at base and 1 ft. high ).  
**NOTE:** Corner not monumented, due to funding restraints.
- 60.207** Point for the North 1/16 section corner of sections 27 and 28, at proportionate distance; ( Record: Sandstone 11 x 11 x 11 ins., marked 1/16 on North face, encircled by a mound of earth 2 ft. diam.at base and 1 ft. high ).  
**NOTE:** Corner not monumented, no verification of ground evidence was performed.
- 80.276** The corner of sections 21, 22, 27, and 28, heretofore described.
- 
- From the corner of sections. 32 and 33, on the South boundary of the Township.
- N. 0° 07.5' E.**, between sections 32 and 33.
- 19.944** Point for the South 1/16 section corner of sections 32, and 33, at proportionate distance; there is no remaining evidence of the original corner.( Record: Sandstone 17 x 13 x 9 ins., marked 1/16 on North face, encircled by a mound of earth 2 ft. diam.at base and 1 ft. high ).  
**NOTE:** Corner not monumented, due to funding restraints.
- 39.888** Point for 1/4 section corner of sections 32 and 33, at proportionate distance; there is no remaining evidence of the original corner. ( Record: Sandstone 14 x 10 x 4 ins. marked 1/4 on North face, encircled by a mound of earth 2 ft. diam. at base and 1 1/2 ft. high ).  
**NOTE:** Corner not monumented, due to funding restraints.
- 59.832** Point for the North 1/16 section corner of sections 32 and 33, at proportionate distance; there is no remaining evidence of the original corner. ( Record: Sandstone 16 x 11 x 5 ins., marked 1/16 on North face, encircled by a mound of earth 2 ft. diam.at base and 1 ft. high ).  
**NOTE:** Corner not monumented, due to funding restraints.
- 79.776** The corner of sections. 28, 29, 32, and 33, heretofore described.
- 
- From the corner of sections 28, 29, 32, and 33.
- N. 0° 18.2' E.**, between sections 28 and 29.
- 20.054** Point for the South 1/16 section corner of sections 28 and 29, at proportionate distance; ( Record: Sandstone 14 x 9 x 7 ins., marked 1/16 on North face, encircled by a mound of earth 2 ft. diam.at base and 1 ft. high ).  
**NOTE:** Corner not monumented, no verification of ground evidence was performed.

INVESTIGATIONAL RETRACEMENT SURVEY FOR SUBDIVISIONAL SECTION  
LINES, T. 1 N., R. 4 W., UTAH SPECIAL MERIDIAN, UTAH

**CHAINS**

- 40.108** Point for 1/4 section corner of sections 28 and 29, at proportionate distance; there is no remaining evidence of the original corner. ( Record: Sandstone 18 x 14 x 5 ins. marked 1/4 on North face, encircled by a mound of earth 2 ft. diam. at base and 1 1/2 ft. high ).  
**NOTE:** Corner not monumented, due to funding restraints.
- 60.162** Point for the North 1/16 section corner of sections 28 and 29, at proportionate distance; ( Record: Sandstone 15 x 9 x 6 ins., marked 1/16 on North face, encircled by a mound of earth 2 ft. diam. at base and 1 ft. high ).  
**NOTE:** Corner not monumented, no verification of ground evidence was performed.
- 80.216** The corner of sections 20, 21, 28, and 29, heretofore described.
- 
- From the corner of sections. 31 and 32, on the South boundary of the Township.
- N. 0° 06.8' E.**, between sections 31 and 32.
- 19.979** Point for the South 1/16 section corner of sections 31 and 32, at proportionate distance; ( Record: Sandstone 18 x 10 x 8 ins., marked 1/16 on North face, encircled by a mound of earth 2 ft. diam. at base and 1 ft. high ).  
**NOTE:** Corner not monumented, no verification of ground evidence was performed.
- 39.959** Point for 1/4 section corner of sections 31 and 32, at proportionate distance; there is no remaining evidence of the original corner. ( Record: Sandstone 18 x 12 x 5 ins. marked 1/4 on North face, encircled by a mound of earth 2 ft. diam. at base and 1 1/2 ft. high ).  
**NOTE:** Corner not monumented, due to funding restraints.
- 59.939** Point for the North 1/16 section corner of sections 31 and 32, at proportionate distance; ( Record: Sandstone 25 x 15 x 7 ins., marked 1/16 on North face, encircled by a mound of earth 2 ft. diam. at base and 1 ft. high ).  
**NOTE:** Corner not monumented, no verification of ground evidence was performed.
- 79.918** The corner of sections 29, 30, 31, 32, heretofore described.
- 
- From the corner of sections 29, 30, 31, and 32.
- N. 0° 10.7' E.**, between sections 29 and 30.
- 20.039** Point for the South 1/16 section corner of sections 29 and 30, at proportionate distance; ( Record: Sandstone 16 x 11 x 7 ins., marked 1/16 on North face, encircled by a mound of earth 2 ft. diam. at base and 1 ft. high ).  
**NOTE:** Corner not monumented, no verification of ground evidence was performed.
- 40.078** Point for 1/4 section corner of sections 29 and 30, at proportionate distance; there is no remaining evidence of the original corner. ( Record: Sandstone 16 x 16 x 8 ins. marked 1/4 on North face, encircled by a mound of earth 2 ft. diam. at base and 1 1/2 ft. high ).  
**NOTE:** Corner not monumented, due to funding restraints.

INVESTIGATIONAL RETRACEMENT SURVEY FOR SUBDIVISIONAL SECTION  
LINES, T. 1 N., R. 4 W., UINTAH SPECIAL MERIDIAN, UTAH

**CHAINS****60.117**

Point for the North 1/16 section corner of sections 29 and 30, at proportionate distance; ( Record: Sandstone 12 x 12 x 4 ins., marked 1/16 on North face, encircled by a mound of earth 2 ft. diam.at base and 1 ft. high ).

**NOTE:** Corner not monumented, no verification of ground evidence was performed.

**80.156**

The corner of sections 19, 20, 29, and 30, heretofore described.

---

Investigational Retracement Survey and Dependent Resurvey  
For the Subdivision of Section 33,  
Township 1 North, Range 4 West, Uintah Special Meridian, Utah

---

Reestablishment of the Survey Executed by D.G. Major in 1882

---

From the South 1/16 section corner of section 33 and 34.

N. 89° 20.8' W., on the East-West subdivisional line of the South half of section 33.

**20.283**

Point for the South-East 1/16 section corner of section 33, determined at the corner of fences projecting North, South and West. This position has long been recognized as the corner by adjacent landowners, and is accepted as the best available evidence of the original corner position. ( Record: Sandstone 18 x 16 x 8 ins., marked 1/16 on East face, encircled by a mound of earth 2 ft. diam.at base and 1 ft. high ).

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a collar of stone, with aluminum cap marked:

SE 1/16 S33  
1992

---

Investigational Retracement Survey  
For the Subdivision of Section 33,  
Township 1 North, Range 4 West, Uintah Special Meridian, Utah

---

Investigational Retracement Survey of the Survey Executed by D.G. Major in 1882

---

From the South-East 1/16 section corner of section 33,

S. 89° 15.9' W., on the East-West subdivisional line of the South half of section 33.

**19.858**

Point for the Center South 1/16 section corner of section 33, at single proportionate distance East and West; there is no remaining evidence of the original corner. ( Record: Sandstone 18 x 12 x 10 ins., marked 1/16 on East face, encircled by a mound of earth 2 ft. diam.at base and 1 ft. high ).

**NOTE:** Corner not monumented, due to funding restraints.



INVESTIGATIONAL RETRACEMENT SURVEY AND DEPENDENT RESURVEY  
FOR THE SUBDIVISION OF SECTION 33,  
T. 1 N., R. 4 W., UTAH SPECIAL MERIDIAN, UTAH

## CHAINS

39.716

Point for the South-West 1/16 section corner of section 33, at single proportionate distance East and West; there is no remaining evidence of the original corner. ( Record: Sandstone 14 x 11 x 7 ins., marked 1/16 on East face, encircled by a mound of earth 2 ft. diam.at base and 1 ft. high ).

NOTE: Corner not monumented, due to funding restraints.

59.574

The South 1/16 section corner of section 32 and 33 heretofore described.

---

Investigational Retracement Survey and Dependent Resurvey  
For the Subdivision of Section 33,  
Township 1 North, Range 4 West, Uintah Special Meridian, Utah

---



---

Reestablishment of the Survey Executed by D.G. Major in 1882

---

From the 1/4 section corner of sections 33 and 34.

N. 89° 17.5' W., on the East-West center line of section 33.

20.214

Point for the Center East 1/16 section corner, determined at the corner of fences projecting South, East and NorthWest. This position has been recognized as the corner by adjacent landowners, and is accepted as the best available evidence of the original corner position. ( Record: Sandstone 16 x 8 x 4 ins., marked 1/16 on East face, encircled by a mound of earth 2 ft. diam.at base and 1 ft. high ).

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

E 1/16  
C ——— C  
S33  
1992

---

Investigational Retracement Survey  
For the Subdivision of Section 33,  
Township 1 North, Range 4 West, Uintah Special Meridian, Utah

---



---

Investigational Retracement Survey of the Survey Executed by D.G. Major in 1882

---

From the Center East 1/16 Section corner.

S. 88° 50.5' W., on the East-West center line of section 33.

INVESTIGATIONAL RETRACEMENT SURVEY  
FOR THE SUBDIVISION OF SECTION 33,  
T. 1 N., R. 4 W., UTAH SPECIAL MERIDIAN, UTAH

**CHAINS**

- 19.872** Point for the Center 1/4 section corner of section 33, at single proportionate distance East and West; there is no remaining evidence of the original corner. ( Record: Sandstone 18 x 14 x 10 ins., marked 1/16 on East face, encircled by a mound of earth 2 ft. diam.at base and 1 ft. high) **NOTE:** Corner not monumented, due to funding restraints.
- 39.744** Point for the Center West 1/16 section corner of section 33, at single proportionate distance East and West; there is no remaining evidence of the original corner. ( Record: Sandstone 12 x 9 x 9 ins., marked 1/16 on East face, encircled by a mound of earth 2 ft. diam.at base and 1 ft. high ). **NOTE:** Corner not monumented, due to funding restraints.
- 59.616** The 1/4 section corner of sections 32 and 33, heretofore described.
- 
- From the North 1/16 section corner of section 33 and 34
- S. 89° 34.9' W, on the East-West subdivision line of the North half of section 33.
- 19.974** Point for the North-East 1/16 section corner of section 33, at single proportionate distance East and West. There is no remaining evidence of the original corner. ( Record: Sandstone 16 x 14 x 10 ins., marked 1/16 on East face, encircled by a mound of earth 2 ft. diam.at base and 1 ft. high ). **NOTE:** Corner not monumented, due to funding restraints.
- 39.948** Point for the Center North 1/16 section corner of section 33, at single proportionate distance East and West; there is no remaining evidence of the original corner. ( Record: Sandstone 14 x 13 x 6 ins., marked 1/16 on East face, encircled by a mound of earth 2 ft. diam.at base and 1 ft. high ). **NOTE:** Corner not monumented, due to funding restraints.
- 59.922** Point for the North-West 1/16 section corner of section 33, at single proportionate distance East and West; there is no remaining evidence of the original corner. ( Record: Sandstone 18 x 16 x 10 ins., marked 1/16 on East face, encircled by a mound of earth 2 ft. diam.at base and 1 ft. high ). **NOTE:** Corner not monumented, due to funding restraints.
- 79.896** The North 1/16 section corner of section 32 and 33 heretofore described.

---

Original Survey of a Portion for the  
Subdivision of Section 33,  
Township 1 North, Range 4 West, Uintah Special Meridian, Utah

---

From the standard East 1/16 section corner of section 33 on the South boundary of the township, hereinbefore described.

N. 0° 08.0' E., the survey of the North-South center line of the South-East 1/4 of section 33.

ORIGINAL SURVEY OF A PORTION FOR THE  
SUBDIVISION OF SECTION 33,  
T. 1 N., R. 4 W., UTAH SPECIAL MERIDIAN, UTAH

**CHAINS**  
**20.509**

The South-East 1/16 section corner of section 33.

---

N. 0° 14.2' E., beginning new measurement.

**20.381**

The center East 1/16 section corner of section 33.

---

Investigational Retracement Survey  
For the Subdivision of Section 34,  
Township 1 North, Range 4 West, Uintah Special Meridian, Utah

---

Investigational Retracement Survey of the Survey Executed by D.G. Major in 1882

---

From the South 1/16 section corner of section 34 and 35

S. 89° 33.3" W, on the East-West subdivision line of the South half of section 34.

**19.926**

Point for the South-East 1/16 section corner of section 34, at single proportionate distance East and West; there is no remaining evidence of the original corner. ( Record: Sandstone 12 x 10 x 8 ins., marked 1/16 on East face, encircled by a mound of earth 2 ft. diam.at base and 1 ft. high ).  
**NOTE:** Corner not monumented, due to funding restraints.

**39.852**

The point for the Center South 1/16 section corner of section 34, determined longitudinally by fence used in determination of standard 1/4 section corner of section 34, and a fence which projects East from the SW 1/16 section corner. This position is accepted as the best available evidence of the true corner position. ( Record: Sandstone 18 x 14 x 10 ins., marked 1/16 on East face, encircled by a mound of earth 2 ft. diam.at base and 1 ft. high ).

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 18 ins. in the ground, in a collar of stone, with aluminum cap marked:

C  
S 1/16 | S34  
C  
1992

Deposit a magnet at base of the aluminum post.

Corner is located 48 links West of a fence which bears N. 1° 35' E. and S. 1° 35' W.

---

INVESTIGATIONAL RETRACEMENT SURVEY AND DEPENDENT RESURVEY  
FOR THE SUBDIVISION OF SECTION 34,  
T. 1 N., R. 4 W., UTAH SPECIAL MERIDIAN, UTAH

**CHAINS**

Investigational Retracement Survey and Dependent Resurvey  
For the Subdivision of Section 34,  
Township 1 North, Range 4 West, Uintah Special Meridian, Utah

Reestablishment of the Survey Executed by D.G. Major in 1882

From the Center South 1/16 section corner of section 34.

N. 89° 21.6' W., on the East-West center line of the South-West 1/4 of section 34.

**20.400**

Point for the South-West 1/16 section corner, determined at the corner of fences projecting East, West and North. This position has long been recognized as the corner by adjacent landowners, and is accepted as the best available evidence of the original corner position.  
( Record: Sandstone 12 x 7 x 6 ins., marked 1/16 on East face, encircled by a mound of earth 2 ft. diam.at base and 1 ft. high ).

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 18 ins. in the ground, in a collar of stone, with aluminum cap marked:

SW 1/16 S34  
1992

From the South-West 1/16 section corner of section 34.

N. 89° 37.5' W., beginning new measurement.

**19.970**

The South 1/16 section corner of section 33 and 34.

Investigational Retracement Survey  
For the Subdivision of Section 34,  
Township 1 North, Range 4 West, Uintah Special Meridian, Utah

Investigational Retracement Survey of the Survey Executed by D.G. Major in 1882

From the 1/4 section corner of section 34 and 35

N. 89° 49.8' W., on the East-West subdivision center line of section 34.

**19.889**

Point for the Center East 1/16 section corner of section 34, at single proportionate distance East and West; there is no remaining evidence of the original corner. ( Record: Sandstone 16 x 10 x 8 ins., marked 1/16 on East face, encircled by a mound of earth 2 ft. diam.at base and 1 ft. high ).

**NOTE:** Corner not monumented, due to funding restraints.

INVESTIGATIONAL RETRACEMENT SURVEY  
FOR THE SUBDIVISION OF SECTION 34,  
T. 1 N., R. 4 W., UINTAH SPECIAL MERIDIAN, UTAH

**CHAINS**  
**39.778**

The point for the Center 1/4 section corner, was determined at the projected intersection of a fence which projects West and the East bank of a ditch which projects South. This ditch indicates its longevity by a substantial growth of White-stem Gooseberry plant in general alignment with ditch and similar to other ditch banks and fences of age, in the area. This position is accepted as the best available evidence of the true corner position. (Record: Sandstone 18 x 10 x 8 ins., marked 1/16 on East face, encircled by a mound of earth 2 ft. diam. at base and 1 1/2 ft. high ).

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 24 ins. in the ground, with aluminum cap marked:

T1N R4W  
C 1/4 S34  
1992

Raise a mound of stone North of the corner.

Corner is located 100 links West of fence which bears N. 1°35' E. and S. 1°35' W.

---

Investigational Retracement Survey and Dependent Resurvey  
For the Subdivision of Section 34,  
Township 1 North, Range 4 West, Uintah Special Meridian, Utah

---

Reestablishment of the Survey Executed by D.G. Major in 1882

---

From the Center 1/4 section corner of section 34.

N. 89° 38.0' W., on the East and West center line of section 34.

**20.351**

Point for the Center W 1/16 section corner, determined at the corner of fences projecting East, West and South. This position has long been recognized as the corner by adjacent landowners and is accepted as the best available evidence of the original corner position.  
(Record: Sandstone 12 x 10 x 8 ins., marked 1/16 on East face, encircled by a mound of earth 2 ft. diam. at base and 1 ft. high ).

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 24 ins. in the ground, with aluminum cap marked:

W 1/16  
C ——— C  
S34  
1992

---

N. 89° 18.5' W., beginning new measurement.

**20.043**

The 1/4 section corner of section 33 and 34.

---

INVESTIGATIONAL RETRACEMENT SURVEY  
FOR THE SUBDIVISION OF SECTION 34,  
T. 1 N., R. 4 W., UTAH SPECIAL MERIDIAN, UTAH

**CHAINS**

Investigational Retracement Survey  
For the Subdivision of Section 34,  
Township 1 North, Range 4 West, Uintah Special Meridian, Utah

Investigational Retracement Survey of the Survey Executed by D.G. Major in 1882

From the North 1/16 section corner of section 34 and 35

N. 89° 54.0' W., on the East-West subdivision line of the North half of section 34.

**20.003** Point for the North-East 1/16 section corner of section 34, at single proportionate distance East and West; there is no remaining evidence of the original corner. ( Record: Sandstone 9 x 8 x 8 ins., marked 1/16 on East face, encircled by a mound of earth 2 ft. diam.at base and 1 ft. high ).  
**NOTE:** Corner not monumented, due to funding restraints.

**40.006** Point for the Center North 1/16 section corner of section 34, at single proportionate distance East and West; there is no remaining evidence of the original corner. ( Record: Sandstone 13 x 11 x 6 ins., marked 1/16 on East face, encircled by a mound of earth 2 ft. diam.at base and 1 ft. high ).  
**NOTE:** Corner not monumented, due to funding restraints.

**60.009** Point for the North-West 1/16 section corner of section 34, at single proportionate distance East and West; there is no remaining evidence of the original corner. ( Record: Sandstone 14 x 9 x 7 ins., marked 1/16 on East face, encircled by a mound of earth 2 ft. diam.at base and 1 ft. high ).  
**NOTE:** Corner not monumented, due to funding restraints.

**80.012** The North 1/16 section corner of section 33 and 34 heretofore described.

Original Survey of a Portion  
For the Subdivision of Section 34,  
Township 1 North, Range 4 West, Uintah Special Meridian, Utah

From the standard 1/4 section corner of section 34, on the South boundary of the township, hereinbefore described.

N. 0° 08.5' E., survey of the North-South center line of section 34.

**19.735** The center South 1/16 section corner of section 34.

N. 0° 06.5' E., beginning new measurement.

**20.351** The center 1/4 section corner of section 34.

ORIGINAL SURVEY OF A PORTION  
FOR THE SUBDIVISION OF SECTION 34,  
T. 1 N., R. 4 W., UTAH SPECIAL MERIDIAN, UTAH

**CHAINS**

From the standard West 1/16 section corner of section 34, on the South boundary of the township, hereinbefore described.

N. 0° 30.5' W., survey of the North-South center line of the South-West 1/4 of section 34.

**20.024**

The South-West 1/16 section corner of section 34.

N. 0° 14.5' E., beginning new measurement.

**20.254**

The center West 1/16 section corner of section 34.

GENERAL DESCRIPTION FOR  
TOWNSHIP 1 NORTH, RANGE 4 WEST, UTAH SPECIAL MERIDIAN, UTAH

The land encompassed in this survey is located about 5 miles North of the town of Altamont. Access is by way of county highway 87, which crosses through Township 1 South, Range 4 West.

From the corner of sections 24, and 25, on the East boundary of the Township, the Altonah Azimuth Mark, bears N. 45° 29' 24" W., for 63.789 chains distance, monumented with a standard disk, set in a boulder nearly flush with ground, and 60 feet West of center line of North-East and South-West graded road, running through section 24. The geographic position is designated as a control station, as determined by Global Positioning System, is as follows:

Latitude: 40° 28' 08.02187" N. Longitude: 110° 17' 17.64770" W.  
Elevation: 7485 Feet. N.A.D. 1983

From Altonah Azimuth Mark, the United States Geological Survey Bench Mark, bears N. 13° 17' 03" W., for 117.338 chains distance, monumented with a United States Geological Survey bronze disk, stamped, "ALTONAH M 1934" cemented in a drill hole in a 3 x 4 foot boulder projecting 3 feet above ground. It is 3 feet higher than the Triangulation Station that bears N 88° 10.3' W, for 0.151 chains distance. The geographic position is designated as a control station, as determined by U.S. Geological Survey, is as follows:

ALTONAH - EAST ( M 1934 ) ( LO1083 ), NORTH AMERICAN DATUM 1983  
( REVISED 1994 )

Latitude: 40° 29' 22.49050" N. Longitude: 110° 17' 40.68173" W.  
Elevation: 8084 Feet NAVD 1988

ALTONAH - EAST ( M 1934 ) ( LO1083 ), NORTH AMERICAN DATUM 1983  
( REVISED 1993 )

Latitude: 40° 29' 22.48964" N. Longitude: 110° 17' 40.68194" W.  
Elevation: 8084 Feet NAVD 1988

## TOWNSHIP 1 NORTH, RANGE 4 W., UTAH SPECIAL MERIDIAN, UTAH

## CHAINS

ALTONAH - EAST ( M 1934 ) ( LO1083 ), NORTH AMERICAN DATUM 1983  
( REVISED 1986 )

Latitude: 40° 29' 22.47139" N. Longitude: 110° 17' 40.67035" W.  
Elevation: 8084 Feet NAVD 1988

ALTONAH - EAST ( M 1934 ) ( LO1083 ), NORTH AMERICAN DATUM 1927

Latitude: 40° 29' 22.65300" N. Longitude: 110° 17' 38.08800" W.  
Elevation: 8081 Feet NGVD 1929

From Altonah Azimuth Mark, the United States Coast and Geodetic Survey Triangulation Station, bears N. 13° 21' 24" W., for 117.375 chains distance, monumented with a United States Coast and Geodetic Survey standard bronze disk, stamped " ALTONAH 1936" cemented in a drill hole within a 2 x 2 ½ foot rock outcrop projecting 3 inches above ground. It is 3 feet lower than the Geological Survey Bench Mark, that bears S 88° 10.3' E, for 0.151 chains distance. The geographic position is designated as a control station, as determined by U.S. Coast and Geodetic Survey, is as follows:

ALTONAH - WEST ( 1936 ) ( LO1084 ), NORTH AMERICAN DATUM 1983  
( REVISED 1994 )

Latitude: 40° 29' 22.49364" N. Longitude: 110° 17' 40.81045" W.  
Elevation: 8081 Feet NAVD 1988

ALTONAH - WEST ( 1936 ) ( LO1084 ), NORTH AMERICAN DATUM 1983  
( REVISED 1993 )

Latitude: 40° 29' 22.49278" N. Longitude: 110° 17' 40.81067" W.  
Elevation: 8081 Feet NAVD 1988

ALTONAH - WEST ( 1936 ) ( LO1084 ), NORTH AMERICAN DATUM 1983  
( REVISED 1986 )

Latitude: 40° 29' 22.47453" N. Longitude: 110° 17' 40.79914" W.  
Elevation: 8081 Feet NAVD 1988

ALTONAH - WEST ( 1936 ) ( LO1084 ), NORTH AMERICAN DATUM 1927

Latitude: 40° 29' 22.65620" N. Longitude: 110° 17' 38.21970" W.  
Elevation: 8078 Feet NGVD 1929



UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD ASSISTANTS**

---

<b>Name</b>	<b>Capacity</b>
Frank C. Profaizer	Supervisory Cadastral Surveyor
Ronald K. Baugh	Supervisory Cadastral Surveyor
M. Ross Workman	Supervisory Cadastral Surveyor
Richard A. Zaninovich	Cadastral Surveyor
Richard A. Houston	Cadastral Surveyor
Steve Hope	Cadastral Surveyor
Ferrel D. Reynolds	Surveying Technician
Phillip Tobler	Surveying Technician
Joseph M. Dhaenens	Surveying Technician

**OFFICE ASSISTANTS**

---

<b>Name</b>	<b>Capacity</b>
David B. Cook	Cartographic Technician
Ruby E. Sugiyama	Surveying Technician

## CERTIFICATE OF SURVEY

I, **Jerry L. Thomas, Cadastral Surveyor**, hereby certify upon honor that, in pursuance of special instructions under Group 781, bearing the date of the 9th day of April, 1992, I have dependently resurveyed the South boundary (Uintah Special Base Line), and a portion of the East boundary along with a portion of the subdivisional lines and the resurvey and survey of the subdivision of sections 33 and 34 by the three mile method. Included with this survey is an Investigational Retracement of the South, East, and West boundaries, the First and Second Latitudinal Section Lines, and a portion of the Subdivisional Lines of 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, and 36, for Township 1 North, Range 4 West, of the Uintah Special Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

March 25, 1999

Date

Jerry L. Thomas  
(Cadastral Surveyor)

Date

(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The foregoing field notes of the dependent resurvey of the South boundary (Uintah Special Base Line), and a portion of the East boundary, along with a portion of the subdivisional lines and the resurvey and survey of the subdivision of sections 33 and 34 by the three mile method. Included with this survey is a Investigational Retracement of the South, East, and West boundaries, the First and Second Latitudinal Section Lines, and a portion of the Subdivisional Lines of 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, and 36, for Township 1 North, Range 4 West, of the Uintah Special Meridian, in the State of Utah,

executed by **Jerry L. Thomas, Cadastral Surveyor**

having been critically examined and found correct, are hereby approved.

March 30, 1999

Date

Daniel W. Wells

(Chief Cadastral Surveyor for Utah)